

ISO/IEC JTC 1/SC 32 N 0745

Date: 2002-01-15

REPLACES: 32N0596

ISO/IEC JTC 1/SC 32

Data Management and Interchange

Secretariat: United States of America (ANSI)

Administered by Pacific Northwest National Laboratory on behalf of ANSI

DOCUMENT TYPE	Text for FCD Ballot
TITLE	ISO/IEC FCD 9075-4:200x Information technology - Database Languages - SQL - Part 4: Persistent Stored Modules (SQL/PSM)
SOURCE	SC 32 Secretariat
PROJECT NUMBER	1.32.03.05.04.00
STATUS	The attached document is hereby submitted for a four-month letter ballot to the National Bodies of ISO/IEC JTC 1/SC 32. The ballot starts 2002-01-29; ITTF must have the document two weeks before the balloting can start.
REFERENCES	
ACTION ID.	LB
REQUESTED ACTION	
DUE DATE	2002-05-29
Number of Pages	167
LANGUAGE USED	English
DISTRIBUTION	P & L Members SC Chair WG Conveners and Secretaries

Douglas Mann, Secretariat, ISO/IEC JTC 1/SC 32

Pacific Northwest National Laboratory *, 901 D Street, SW., Suite 900, Washington, DC, 20024-2115, United States of America

Telephone: +1 703 236-1422; Facsimile; +1 703 527-5640; E-mail: MannD@battelle.org

available from the JTC 1/SC 32 WebSite <http://www.jtc1sc32.org/>

*Pacific Northwest National Laboratory (PNL) administers the ISO/IEC JTC 1/SC 32 Secretariat on behalf of ANSI

ISO/IEC JTC 1/SC 32

Date: 2002-01-11

ISO/IEC 9075-4:200x(E)

ISO/IEC JTC 1/SC 32/WG 3

Secretariat: United States of America (ANSI)

**Information technology — Database languages — SQL — Part 4: Persistent
Stored Modules (SQL/PSM)**

*Technologies de l'information — Langages de base de donnée — SQL — Partie 4: «Persistants Enregistrés
Modules?» (SQL/PSM)*

Document type: International standard
Document subtype:
Document stage: (20) Working Draft
Document language: E

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, photocopying, recording, or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to ISO at the address below or ISO's member body in the country of the requester.

*Copyright Manager
ISO Central Secretariat
1 rue de Varembé
1211 Geneva 20 Switzerland
tel. +41 22 749 0111
fax +41 22 734 1079
internet: iso@iso.ch*

Reproduction may be subject to royalty payments or a licensing agreement.

Violaters may be prosecuted.

Contents	Page
Foreword	viii
Introduction	ix
1 Scope	1
2 Normative references	3
2.1 JTC1 standards	3
3 Definitions, notations, and conventions	5
3.1 Definitions	5
3.1.1 Definitions provided in Part 4	5
3.2 Notations	5
3.3 Conventions	5
3.3.1 Use of terms	5
3.3.1.1 Exceptions	5
3.3.1.2 Other terms	6
3.3.2 General Rules not terminated on exception conditions	6
3.4 Object identifier for Database Language SQL	6
4 Concepts	9
4.1 SQL-server modules	9
4.2 SQL-invoked routines	10
4.3 SQL-paths	10
4.4 Tables	10
4.4.1 Types of tables	10
4.5 SQL-schemas	11
4.6 Host parameters	11
4.6.1 Status parameters	11
4.7 Diagnostics area	11
4.8 Cursors	11
4.9 Condition handling	12
4.10 SQL-statements	13
4.10.1 SQL-statements classified by function	13
4.10.2 Embeddable SQL-statements	14
4.10.3 Preparable and immediately executable SQL-statements	15
4.10.4 Directly executable SQL-statements	15

4.10.5	Iterated SQL-statements	15
4.10.6	SQL-statements and transaction states	16
4.10.7	Compound statements	16
4.10.8	SQL-statement atomicity and statement execution contexts	16
4.11	Basic security model	17
4.11.1	Privileges	17
4.12	SQL-sessions	17
5	Lexical elements	19
5.1	<token> and <separator>	19
5.2	Names and identifiers	21
6	Scalar expressions	25
6.1	<value specification> and <target specification>	25
6.2	<identifier chain>	26
6.3	<SQL variable reference>	28
7	Query expressions	29
7.1	<query specification>	29
8	Additional common elements	31
8.1	<routine invocation>	31
8.2	<sqlstate value>	33
9	Schema definition and manipulation	35
9.1	<schema definition>	35
9.2	<drop schema statement>	36
9.3	<default clause>	37
9.4	<drop column scope clause>	38
9.5	<drop column definition>	39
9.6	<drop table constraint definition>	40
9.7	<drop table statement>	41
9.8	<view definition>	42
9.9	<drop view statement>	43
9.10	<drop domain statement>	44
9.11	<drop character set statement>	45
9.12	<drop collation statement>	46
9.13	<drop transliteration statement>	47
9.14	<assertion definition>	48
9.15	<drop assertion statement>	49
9.16	<trigger definition>	50
9.17	<drop user-defined ordering statement>	51
9.18	<SQL-server module definition>	52
9.19	<drop module statement>	55
9.20	<drop data type statement>	56
9.21	<SQL-invoked routine>	57
9.22	<drop routine statement>	59

9.23	<drop user-defined cast statement>	60
10	Access control	61
10.1	<grant statement>	61
10.2	<privileges>	62
10.3	<revoke statement>	63
11	SQL-client modules	67
11.1	Calls to an <externally-invoked procedure>	67
11.2	<SQL procedure statement>	68
12	Data manipulation	71
12.1	<open statement>	71
12.2	<fetch statement>	72
12.3	<close statement>	73
12.4	<select statement: single row>	74
12.5	<delete statement: positioned>	75
12.6	<update statement: positioned>	76
12.7	<temporary table declaration>	77
13	Control statements	79
13.1	<compound statement>	79
13.2	<handler declaration>	83
13.3	<condition declaration>	87
13.4	<SQL variable declaration>	88
13.5	<assignment statement>	89
13.6	<case statement>	94
13.7	<if statement>	97
13.8	<iterate statement>	99
13.9	<leave statement>	100
13.10	<loop statement>	101
13.11	<while statement>	102
13.12	<repeat statement>	103
13.13	<for statement>	104
14	Dynamic SQL	107
14.1	<prepare statement>	107
15	Embedded SQL	109
15.1	<embedded SQL host program>	109
16	Diagnostics management	111
16.1	<get diagnostics statement>	111
16.2	<signal statement>	114
16.3	<resignal statement>	116

17	Information Schema	119
17.1	MODULE_COLUMN_USAGE view	119
17.2	MODULE_PRIVILEGES view	120
17.3	MODULE_TABLE_USAGE view	121
17.4	MODULES view	122
17.5	ROLE_MODULE_GRANTS view	123
17.6	Short name views	124
18	Definition Schema	125
18.1	MODULE_COLUMN_USAGE base table	125
18.2	MODULE_PRIVILEGES base table	127
18.3	MODULE_TABLE_USAGE base table	129
18.4	MODULES base table	130
19	Status codes	133
19.1	SQLSTATE	133
20	Conformance	135
20.1	Claims of conformance	135
Annex A	SQL Conformance Summary	137
Annex B	Implementation-defined elements	139
Annex C	Implementation-dependent elements	141
Annex D	Deprecated features	143
Annex E	Incompatibilities with ISO/IEC 9075-4:1999	145
Annex F	SQL Feature Taxonomy	147
Index		149

TABLES

Tables		Page
1	<identifier>s for use with <get diagnostics statement>	111
2	SQL-statement codes	112
3	SQLSTATE class and subclass values	133
4	Feature taxonomy for features outside Core SQL	147

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 9075-4 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 32, *Data management and interchange*.

This second edition of this part of ISO/IEC 9075 cancels and replaces the first edition, ISO/IEC 9075-4:1996.

ISO/IEC 9075 consists of the following parts, under the general title *Information technology — Database languages — SQL*:

- Part 1: Framework (SQL/Framework)
- Part 2: Foundation (SQL/Foundation)
- Part 3: Call-Level Interface (SQL/CLI)
- Part 4: Persistent Stored Modules (SQL/PSM)
- 1 list element deleted.
- Part 9: Management of External Data (SQL/MED)
- Part 10: Object Language Bindings (SQL/OLB)
- Part 11: Information and Definition Schema (SQL/Schemata)
- Part 13: Routines and Types Using the Java™ Programming Language (SQL/JRT)
- Part 14: XML-Related Specifications (SQL/XML)

Annexes A, B, C, D, E, and F of this part of ISO/IEC 9075 are for information only.

Introduction

The organization of this part of ISO/IEC 9075 is as follows:

- 1) Clause 1, “Scope”, specifies the scope of this part of ISO/IEC 9075.
- 2) Clause 2, “Normative references”, identifies additional standards that, through reference in this part of ISO/IEC 9075, constitute provisions of this part of ISO/IEC 9075.
- 3) Clause 3, “Definitions, notations, and conventions”, defines the notations and conventions used in this part of ISO/IEC 9075.
- 4) Clause 4, “Concepts”, presents concepts used in the definition of persistent stored modules.
- 5) Clause 5, “Lexical elements”, defines a number of lexical elements used in the definition of persistent stored modules.
- 6) Clause 6, “Scalar expressions”, defines a number of scalar expressions used in the definition of persistent stored modules.
- 7) Clause 7, “Query expressions”, defines the elements of the language that produce rows and tables of data as used in persistent stored modules.
- 8) Clause 8, “Additional common elements”, defines additional common elements used in the definition of persistent stored modules.
- 9) Clause 9, “Schema definition and manipulation”, defines the schema definition and manipulation statements associated with the definition of persistent stored modules.
- 10) Clause 10, “Access control”, defines facilities for controlling access to SQL-data.
- 11) Clause 11, “SQL-client modules”, defines the facilities for using persistent stored modules.
- 12) Clause 12, “Data manipulation”, defines data manipulation operations associated with persistent stored modules.
- 13) Clause 13, “Control statements”, defines the control statements used with persistent stored modules.
- 14) Clause 14, “Dynamic SQL”, defines the facilities for executing SQL-statements dynamically in the context of persistent stored modules.
- 15) Clause 15, “Embedded SQL”, defines the host language embeddings.
- 16) Clause 16, “Diagnostics management”, defines enhancements to the facilities used with persistent stored modules.
- 17) Clause 17, “Information Schema”, defines the Information and Definition Schema objects associated with persistent stored modules.
- 18) Clause 18, “Definition Schema”, defines base tables on which the viewed tables containing schema information depend.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

- 19) Clause 19, “Status codes”, defines SQLSTATE values related to persistent stored modules.
- 20) Clause 20, “Conformance”, defines the criteria for conformance to this part of ISO/IEC 9075.
- 21) Annex A, “SQL Conformance Summary”, is an informative Annex. It summarizes the conformance requirements of the SQL language.
- 22) Annex B, “Implementation-defined elements”, is an informative Annex. It lists those features for which the body of this part of ISO/IEC 9075 states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or any other behavior is partly or wholly implementation-defined.
- 23) Annex C, “Implementation-dependent elements”, is an informative Annex. It lists those features for which the body of this part of ISO/IEC 9075 states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or any other behavior is partly or wholly implementation-dependent.
- 24) Annex D, “Deprecated features”, is an informative Annex. It lists features that the responsible Technical Committee intends will not appear in a future revised version of ISO/IEC 9075.
- 25) Annex E, “Incompatibilities with ISO/IEC 9075-4:1999”, is an informative Annex. It lists the incompatibilities between this edition of this part of ISO/IEC 9075 and ISO/IEC 9075-4:1996.
- 26) Annex F, “SQL Feature Taxonomy”, is an informative Annex. It identifies features of the SQL language specified in this part of ISO/IEC 9075 by a numeric identifier and a short descriptive name. This taxonomy is used to specify conformance to Core SQL and may be used to develop other profiles involving the SQL language.

In the text of this part of ISO/IEC 9075, Clauses begin a new odd-numbered page, and in Clause 5, “Lexical elements”, through Clause 20, “Conformance”, Subclauses begin a new page. Any resulting blank space is not significant.

Information technology — Database languages — SQL —

Part 4: Persistent Stored Modules (SQL/PSM)

1 Scope

This part of International Standard ISO/IEC 9075 specifies the syntax and semantics of a database language for declaring and maintaining persistent database language routines in SQL-server modules.

The database language for <externally-invoked procedure>s and <SQL-invoked routine>s includes:

- The specification of statements to direct the flow of control.
- The assignment of the result of expressions to variables and parameters.
- The specification of condition handlers that allow SQL-invoked routines to deal with various conditions that arise during their execution.
- The specification of statements to signal and resignal conditions.
- The declaration of local cursors.
- The declaration of local variables.

It also includes the definition of the Information Schema tables that contain schema information pertaining to SQL-server modules and SQL-invoked routines.

- 1 Note deleted.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

2 Normative references

The following normative documents contain provisions that, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

2.1 JTC1 standards

ISO 8824-1:1995, *Information technology — Specification of Abstract Syntax Notation One (ASN.1) — Part 1: Specification of basic notation*

- 1 list element deleted.

ISO/IEC FCD 9075-1:200x, *Information technology — Database languages — SQL — Part 1: Framework (SQL/Framework)*.

ISO/IEC FCD 9075-2:200x, *Information technology — Database languages — SQL — Part 2: Foundation (SQL/Foundation)*.

- 3 list elements deleted.

ISO/IEC FCD 9075-11:200x, *Information technology — Database languages — SQL — Part 11: Information and Definition Schemas (SQL/Schemata)*.

- 2 list elements deleted.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

3 Definitions, notations, and conventions

This Clause modifies Clause 3, "Definitions, notations, and conventions", in ISO/IEC 9075-2.

3.1 Definitions

This Subclause modifies Subclause 3.1, "Definitions", in ISO/IEC 9075-2.

3.1.1 Definitions provided in Part 4

Insert this paragraph For the purposes of this part of ISO/IEC 9075, the definitions given in ISO/IEC 9075-1 and ISO/IEC 9075-2 apply.

3.2 Notations

This Subclause modifies Subclause 3.2, "Notation", in ISO/IEC 9075-2.

Insert this paragraph The syntax notation used in this part of ISO/IEC 9075 is an extended version of BNF ("Backus Normal Form" or "Backus Naur Form"). This version of BNF is fully described in Subclause 6.1, "Notation", of ISO/IEC 9075-1.

3.3 Conventions

This Subclause modifies Subclause 3.3, "Conventions", in ISO/IEC 9075-2.

Insert this paragraph Except as otherwise specified in this part of ISO/IEC 9075, the conventions used in this part of ISO/IEC 9075 are identical to those described in ISO/IEC 9075-1 and ISO/IEC 9075-2.

3.3.1 Use of terms

This Subclause modifies Subclause 3.3.1, "Use of terms", in ISO/IEC 9075-2.

3.3.1.1 Exceptions

This Subclause modifies Subclause 6.2.3.7, "Exceptions", in ISO/IEC 9075-1.

Insert this paragraph The phrase "C is re-raised by S" is used in General Rules and elsewhere to indicate that C, a condition raised by an SQL-statement executed during execution of S, is raised again by S.

3.3 Conventions

3.3.1.2 Other terms

This Subclause modifies Subclause 3.3.1.1, "Other terms", in ISO/IEC 9075-2.

Insert this paragraph An SQL-statement *S1* is said to be executed as a *direct result of executing an <SQL control statement> S2* if *S2* contains *S1*.

Insert this paragraph The phrase “The scope of a <handler declaration> contained in a/an *Y* is that *Y*, excluding every <SQL schema statement> contained in that *Y*” means that the scope of the <handler declaration> does not extend to SQL-statements contained in such an <SQL schema statement>; it does, however, extend to the <SQL schema statement> itself.

3.3.2 General Rules not terminated on exception conditions

This Subclause modifies Subclause 6.2.3.8, "General Rules not terminated on exception conditions", in ISO/IEC 9075-1.

Insert into the 1st paragraph

- Subclause 13.1, “<compound statement>”.
- Subclause 13.2, “<handler declaration>”.

3.4 Object identifier for Database Language SQL

This Subclause modifies Subclause 8.1.5, "Claims of conformance", in ISO/IEC 9075-1.

The object identifier for Database Language SQL is defined in ISO/IEC 9075-1 in Subclause 6.3, "Object identifier for Database Language SQL", with the following additions and modifications:

Format

```
<SQL object identifier> ::=
    <SQL provenance> <SQL variant>
    <SQL provenance> <SQL variant> <SQL parts>
```

```
<SQL parts> ::=
    4 | sqlpsm1996 <left paren> 4 <right paren>
```

```
<Part 4 yes> ::=
    <Part 4 conformance> <Part 4 module>
```

```
<Part 4 conformance> ::=
    4
    | sqlpsm1999 <left paren> 4 <right paren>
    | sqlpsm200n <left paren> 4 <right paren>
```

```
<Part 4 module> ::=
    <Part 4 module yes>
    | <Part 4 module no>
```

```
<Part 4 module yes> ::=
    1 | moduleyes <left paren> 1 <right paren>
```

```
<Part 4 module no> ::=
    0 | moduleno <left paren> 0 <right paren>
```

Syntax Rules

- 1) Specification of <Part 4 yes> implies that conformance to ISO/IEC 9075-4 is claimed.
- 2) Specification of <Part 4 module yes> implies that conformance to Feature P001, “Stored modules”, is claimed.
- 3) Specification of <Part 4 module no> implies that conformance to Feature P001, “Stored modules”, is not claimed.
- 4) If <SQL parts> is specified, then <SQL edition> shall specify <1992>.
- 5) If <Part 4 conformance> specifies `sqlpsm1999`, then <SQL edition> shall specify <1999>.
- 6) If <Part 3 conformance> specifies `sqlpsm200n`, then <SQL edition> shall specify <200n>.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

4 Concepts

This Clause modifies Clause 4, "Concepts", in ISO/IEC 9075-2.

4.1 SQL-server modules

An *SQL-server module* is a persistent object defined in a schema and identified by an <SQL-server module name>. SQL-server modules are created with <SQL-server module definition>s and destroyed with <drop module statement>s and by <drop schema statement>s that destroy the schemas that contain them.

An <SQL-server module definition> contains an <SQL-server module name>, an optional <SQL-server module character set specification>, an optional <SQL-server module schema clause>, an optional <SQL-server module path specification>, zero or more declared local temporary tables specified by <temporary table declaration>s, and one or more <SQL-invoked routine>s.

The <SQL-server module name> of an SQL-server module is a <schema qualified name>. The character set specified by the <SQL-server module character set specification> identifies the character repertoire used for expressing the names of schema objects used in the <SQL-server module definition>. The <default schema name> specified by the <SQL-server module schema clause> identifies the schema name used for implicit qualification of unqualified names appearing in the <SQL-server module definition>. The SQL-invoked routines of an SQL-server module are invoked only from SQL-statements.

An SQL-server module has an *SQL-server module authorization identifier*, which is set to the authorization identifier of the owner of the schema that contains the SQL-server module at the time the SQL-server module is created. The SQL-server module authorization identifier acts as the current authorization identifier for privilege determination for the SQL objects, if any, contained in the SQL-server module.

An SQL-server module is described by an SQL-server module descriptor. An SQL-server module descriptor includes:

- The SQL-server module name of the SQL-server module.
- The descriptor of the character set in which the SQL-server module is represented.
- The default schema name used for implicit qualification of unqualified names in the SQL-server module.
- The SQL-server module authorization identifier of the SQL-server module.
- The list of schema names contained in the <SQL-server module path specification>.
- The table descriptor of every local temporary table declared in the SQL-server module.
- The descriptor of every SQL-invoked routine contained in the SQL-server module.
- The text of the <SQL-server module definition>.

4.2 SQL-invoked routines

This Subclause modifies Subclause 4.28, "SQL-invoked routines", in ISO/IEC 9075-2.

Replace 2nd paragraph An SQL-invoked routine is either a component of an <SQL-server module definition> or an element of an SQL-schema. An SQL-invoked routine that is an element of an SQL-schema is called a schema-level routine.

Replace 28th paragraph An SQL-invoked routine has a *routine SQL-path*, which is inherited from its containing SQL-server module or schema, the current SQL-session, or the containing SQL-client module.

Insert in the 30th paragraph — If the SQL-invoked routine is not a schema-level routine, then the <SQL-server module name> of the SQL-server module that includes the SQL-invoked routine and the <schema name> of the schema that includes the SQL-server module.

4.3 SQL-paths

This Subclause modifies Subclause 4.30, "SQL-paths", in ISO/IEC 9075-2.

Replace 3rd paragraph The value specified by CURRENT_PATH is the value of the SQL-path of the current SQL-session. This SQL-path is used to search for the subject routine of a <routine invocation> whose <routine name> does not contain a <schema name> when the <routine invocation> is contained in <preparable statement>s that are prepared in the current SQL-session by either an <execute immediate statement> or a <prepare statement>, or contained in <direct SQL statement>s that are invoked directly. The definition of SQL-schemas and SQL-server modules specify an SQL-path that is used to search for the subject routine of a <routine invocation> whose <routine name>s do not contain a <schema name> when the <routine invocation> is contained respectively in the <schema definition> or the <SQL-server module definition>.

4.4 Tables

This Subclause modifies Subclause 4.15, "Tables", in ISO/IEC 9075-2.

4.4.1 Types of tables

This Subclause modifies Subclause 4.15.1, "Types of tables", in ISO/IEC 9075-2.

Insert this paragraph A declared local temporary table may be declared in an SQL-server module.

Insert this paragraph A declared local temporary table that is declared in an SQL-server module is a named table defined by a <temporary table declaration> that is effectively materialized the first time any <module routine> in the <SQL-server module definition> that contains the <temporary table declaration> is executed.

Insert this paragraph A declared local temporary table is accessible only by <module routine>s in the <SQL-server module definition> that contains the <temporary table declaration>. The effective <schema name> of the <schema qualified name> of the declared local temporary table may be thought of as the implementation-dependent SQL-session identifier associated with the SQL-session and the name of the <SQL-server module definition> that contains the <temporary table declaration>.

4.5 SQL-schemas

This Subclause modifies Subclause 4.21, "SQL-schemas", in ISO/IEC 9075-2.

Insert into the 2nd paragraph

— An SQL-server module descriptor.

4.6 Host parameters

This Subclause modifies Subclause 4.31, "Host parameters", in ISO/IEC 9075-2.

4.6.1 Status parameters

This Subclause modifies Subclause 4.31.1, "Status parameters", in ISO/IEC 9075-2.

Insert this paragraph Exception conditions or completion conditions may be raised during the execution of an <SQL procedure statement>. One of the conditions becomes the active condition when the <SQL procedure statement> terminates; the *active condition* is the condition returned in SQLSTATE. If the active condition is an exception condition, then it is called the *active exception condition*. If the active condition is a completion condition, then it is called the *active completion condition*.

Insert this paragraph If the <SQL procedure statement> is a <compound statement>, then the active condition may result from the action of some exception handler specified in the <compound statement>.

4.7 Diagnostics area

This Subclause modifies Subclause 4.32, "Diagnostics area", in ISO/IEC 9075-2.

Insert this paragraph Information about a completion or exception condition is placed into one or more condition areas of the first diagnostics area before any handler is activated. The diagnostics area stack is then pushed so that the handler can access that information even while its own execution is causing the first diagnostics area to be modified.

Insert this paragraph The first diagnostics area is emptied during the execution of a <signal statement>. Information is added to the first diagnostics area during the execution of a <resignal statement>.

4.8 Cursors

This Subclause modifies Subclause 4.34, "Cursors", in ISO/IEC 9075-2.

Insert this paragraph For every <declare cursor> in a <compound statement>, a cursor is effectively created each time the <compound statement> is executed and, unless the cursor is an open result set cursor, destroyed when that execution completes.

4.9 Condition handling

4.9 Condition handling

Condition handling is the method of handling exception and completion conditions in SQL/PSM. Condition handling provides a *<handler declaration>* to define a handler, specifying its type, the exception and completion conditions it can resolve, and the action it takes to do so. Condition handling also provides the ability to explicitly signal exception and completion conditions.

*<handler declaration>*s specify the handling of exception and completion conditions. *<handler declaration>*s are optionally specified in *<compound statement>*s. The scope of a *<handler declaration>* specified in *<compound statement>* *CS* is *CS*, excluding every *<SQL schema statement>* contained in *CS*.

A *<handler declaration>* associates one or more conditions with a handler action. The handler action is an *<SQL procedure statement>*.

A *general <handler declaration>* is one that is associated with the *<condition value>*s *SQLEXCEPTION*, *SQLWARNING*, or *NOT FOUND*. All other *<handler declaration>*s are *specific <handler declaration>*s.

A condition represents an error or informational state caused by execution of an *<SQL procedure statement>*. Conditions are raised to provide information in a diagnostics area about the execution of an *<SQL procedure statement>*.

A *<condition declaration>* is used to declare a *<condition name>*, and to optionally associate it with an *SQLSTATE* value. If a *<condition declaration>* does not specify an *SQLSTATE* value, it declares a *user-defined exception condition*. *<condition name>*s can be used in *<handler declaration>*s, *<signal statement>*s, and *<resignal statement>*s.

When the *<compound statement>* containing a *<handler declaration>* is executed, a handler is created for the conditions associated with that *<handler declaration>*. A created handler is *activated* when it is the most appropriate handler for an exception or completion condition that has been raised by an SQL-statement. Such a handler is an *active* handler.

The *most appropriate* handler is determined during execution of an implicit or explicit *<resignal statement>*. An implicit *<resignal statement>* is executed when a *<compound statement>* or *<handler action>* completes with a condition other than *successful completion*.

If there is no most appropriate handler and the condition is an exception condition, then the SQL-statement raising the exception condition is terminated with that exception condition. This type of exception condition is called an *unhandled exception condition*. Unhandled exception conditions are examined at the next visible scope for handling. If an exception condition remains unhandled at the outermost *<externally-invoked procedure>* or *<direct SQL statement>*, it is seen by the SQL-client. Even if the SQL-client resolves the exception condition, execution is not resumed in the SQL-server where the exception condition was raised.

If there is no most appropriate handler and the condition is a completion condition, then execution is resumed as specified in Subclause 6.2.3.7, "Exceptions", in ISO/IEC 9075-1. This type of completion condition is called an *unhandled completion condition*.

A handler type specifies *CONTINUE*, *EXIT*, or *UNDO*.

If a handler type specifies *CONTINUE*, then, when the handler is activated, it will:

- Push the diagnostics area stack.
- Execute the handler action.
- Pop the diagnostics area stack.

- Cause the SQL-session to continue as it would have done if execution of the innermost executing statement that raised the condition had completed.

If a handler type specifies EXIT, then, when the handler is activated, it will:

- Push the diagnostics area stack.
- Execute the handler action.
- Pop the diagnostics area stack.
- Implicitly LEAVE the <compound statement> for which the handler was created, with no active exception condition.

If a handler type specifies UNDO, then, when the handler is activated, it will:

- Push the diagnostics area stack.
- Roll back all of the changes to SQL-data or to schemas by the execution of every SQL-statement contained in the SQL-statement list of the <compound statement> at the scope of the handler and cancel any <SQL procedure statement>s triggered by the execution of such statements.
- Pop the diagnostics area stack.
- Execute the handler action.
- Cause the SQL-session to continue as it would have done if execution of the <compound statement> for which the handler was created had completed.

If a <handler action> completes with a completion condition: *successful completion*, then it was able to resolve the condition, and execution resumes as specified in Subclause 13.2, “<handler declaration>”.

If a <handler action> completes with an exception or completion condition other than *successful completion*, then an implicit <resignal statement> is executed. The <resignal statement> determines whether there is another <handler declaration> that can resolve the condition.

4.10 SQL-statements

This Subclause modifies Subclause 4.35, "SQL-statements", in ISO/IEC 9075-2.

4.10.1 SQL-statements classified by function

This Subclause modifies Subclause 4.35.2, "SQL-statements classified by function", in ISO/IEC 9075-2.

Insert this paragraph The following are additional main classes of SQL-statements:

- SQL-control declarations

Insert this paragraph The following are additional SQL-schema statements:

- <SQL-server module definition>

4.10 SQL-statements

— <drop module statement>

Insert this paragraph The following are additional SQL-control statements:

— <compound statement>

— <case statement>

— <if statement>

— <iterate statement>

— <leave statement>

— <loop statement>

— <while statement>

— <repeat statement>

— <for statement>

— <assignment statement>

Insert this paragraph The following are the SQL-control declarations:

— <condition declaration>

— <handler declaration>

— <SQL variable declaration>

Insert this paragraph The following are additional SQL-diagnostics statements:

— <signal statement>

— <resignal statement>

4.10.2 Embeddable SQL-statements

This Subclause modifies Subclause 4.35.6, "Embeddable SQL-statements", in ISO/IEC 9075-2.

Insert this paragraph The following are additional SQL-statements that are embeddable in an <embedded SQL host program> and that may be the <SQL procedure statement> in an <externally-invoked procedure> in an SQL-client module:

— All SQL-control statements

NOTE 1 – SQL-control declarations contained in (for example) <compound statement>s are permitted, even when the containing SQL-statement is embedded in an <embedded SQL host program>.

4.10.3 Preparable and immediately executable SQL-statements

This Subclause modifies Subclause 4.35.7, "Preparable and immediately executable SQL-statements", in ISO/IEC 9075-2.

Insert this paragraph Consequently, the following SQL-control statements are not preparable:

- <compound statement>
- <case statement>
- <if statement>
- <iterate statement>
- <leave statement>
- <loop statement>
- <while statement>
- <repeat statement>
- <for statement>
- <assignment statement>

Insert this paragraph Consequently, the following SQL-control declarations are not preparable:

- <condition declaration>
- <handler declaration>
- <SQL variable declaration>

4.10.4 Directly executable SQL-statements

This Subclause modifies Subclause 4.35.8, "Directly executable SQL-statements", in ISO/IEC 9075-2.

Insert this paragraph The following are additional SQL-statements that may be executed directly:

- All SQL-control statements

4.10.5 Iterated SQL-statements

The following are the iterated SQL-statements:

- <loop statement>
- <while statement>
- <repeat statement>
- <for statement>

4.10 SQL-statements

4.10.6 SQL-statements and transaction states

This Subclause modifies Subclause 4.35.4, "SQL-statements and transaction states", in ISO/IEC 9075-2.

Insert this paragraph The following additional SQL-statement is a transaction-initiating SQL-statement:

- <for statement>

Insert this paragraph The following additional SQL-statement is not a transaction-initiating SQL-statement:

- <iterate statement>
- <leave statement>

Insert this paragraph The following additional SQL-statements are possibly transaction-initiating SQL-statements:

- SQL-control statements other than:
 - <for statement>
 - <iterate statement>
 - <leave statement>

4.10.7 Compound statements

A compound statement allows a sequence of SQL-statements to be considered as a single SQL-statement. A compound statement also defines a local scope in which SQL-variables, condition handlers, and cursors can be declared. See Subclause 13.1, "<compound statement>".

4.10.8 SQL-statement atomicity and statement execution contexts

This Subclause modifies Subclause 4.35.5, "SQL-statement atomicity and statement execution contexts", in ISO/IEC 9075-2.

Add to the list of non-atomic SQL-statements

- <assignment statement>.
- <case statement>.
- <compound statement>, unless BEGIN ATOMIC is specified.
- <for statement>.
- <if statement>.
- <loop statement>.
- <repeat statement>.

— <while statement>.

4.11 Basic security model

This Subclause modifies Subclause 4.36, "Basic security model", in ISO/IEC 9075-2.

4.11.1 Privileges

This Subclause modifies Subclause 4.36.2, "Privileges", in ISO/IEC 9075-2.

Insert this paragraph A privilege further authorizes a given category of <action> to be performed on a specified SQL-server module by a specified <authorization identifier>.

Insert this paragraph An *execute privilege descriptor* may also identify the existence of a privilege on the SQL-server module identified by the privilege descriptor.

Insert this paragraph The identification included in an EXECUTE privilege descriptor may also identify the SQL-server module described by the descriptor.

Insert this paragraph Individual SQL-invoked routines contained in an SQL-server module cannot be associated with EXECUTE privilege descriptors. Only schema-level routines and SQL-server modules are associated with EXECUTE privilege descriptors.

NOTE 2 – “schema-level routine” is defined in Subclause 11.50, "<SQL-invoked routine>", in ISO/IEC 9075-2.

4.12 SQL-sessions

This Subclause modifies Subclause 4.39, "SQL-sessions", in ISO/IEC 9075-2.

Insert this paragraph Certain operations during an SQL-session *SS* are possible only when *SS* is in *condition handling mode*. This mode becomes in effect when execution of an SQL-statement has completed to the extent that all diagnostics information pertaining to that execution is recorded in the first diagnostics area. Condition handling mode ceases to be in effect when execution of the next SQL-statement begins.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

5 Lexical elements

This Clause modifies Clause 5, "Lexical elements", in ISO/IEC 9075-2.

5.1 <token> and <separator>

This Subclause modifies Subclause 5.2, "<token> and <separator>", in ISO/IEC 9075-2.

Function

Specify lexical units (tokens and separators) that participate in SQL language.

Format

```
<non-reserved word> ::=
    !! All alternatives from ISO/IEC 9075-2
    | CONDITION_IDENTIFIER
    | STACKED
```

```
<reserved word> ::=
    !! All alternatives from ISO/IEC 9075-2
```

```
    | DO
    | ELSEIF | EXIT
    | HANDLER
    | IF | ITERATE
    | LEAVE | LOOP
    | REPEAT | RESIGNAL
    | SIGNAL
    | UNDO | UNTIL
    | WHILE
```

Syntax Rules

No additional Syntax Rules.

SC32 N00745 = WG3:VIE-006 = H2-2002-008
5.1 <token> and <separator>

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

5.2 Names and identifiers

This Subclause modifies Subclause 5.4, "Names and identifiers", in ISO/IEC 9075-2.

Function

Specify names.

Format

```
<SQL-server module name> ::=  
    <schema qualified name>
```

```
<SQL variable name> ::=  
    <identifier>
```

```
<condition name> ::=  
    <identifier>
```

Syntax Rules

- 1) Replace SR4)a) If the <local or schema qualified name> is contained, without an intervening <schema definition> or <SQL-server module definition>, in a <preparable statement> that is prepared in the current SQL-session by an <execute immediate statement> or a <prepare statement> or in a <direct SQL statement> that is invoked directly, then the default <unqualified schema name> for the SQL-session is implicit.
- 2) Insert before SR4)b) If the <local or schema qualified name> is contained in an <SQL-server module definition> without an intervening <schema definition>, then the <default schema name> that is specified or implicit in the <SQL-server module definition> is implicit.
- 3) Replace SR11)a) If the <schema qualified name> is contained, without an intervening <schema definition> or <SQL-server module definition>, in a <preparable statement> that is prepared in the current SQL-session by an <execute immediate statement> or a <prepare statement> or in a <direct SQL statement> that is invoked directly, then the default <unqualified schema name> for the SQL-session is implicit.
- 4) Insert before SR11)b) If the <schema qualified name> is contained in an <SQL-server module definition> without an intervening <schema definition>, then the <default schema name> that is specified or implicit in the <SQL-server module definition> is implicit.
- 5) Replace SR8) If <user-defined type name> *UDTN* with a <qualified identifier> *QI* is specified, then
Case:
 - a) If *UDTN* is simply contained in <path-resolved user-defined type name>, then
Case:
 - i) If *UDTN* contains a <schema name> *SN*, then the schema identified by *SN* shall contain the descriptor of a user-defined type *UDT* such that the <qualified identifier> of *UDT* is equivalent to *QI*. *UDT* is the user-defined type identified by *UDTN*.

5.2 Names and identifiers

ii) Otherwise:

1) Case:

- A) If *UDTN* is contained, without an intervening <schema definition> or <SQL-server module definition>, in a <preparable statement> that is prepared in the current SQL-session by an <execute immediate statement> or by a <prepare statement> or in a <direct SQL statement> that is invoked directly, then let *DP* be the SQL-path of the current SQL-session.
- B) If *UDTN* is contained in an <SQL-server module definition> without in intervening <schema definition>, then let *DP* be the SQL-path of that <SQL-server module definition>.
- C) If *UDTN* is contained in a <schema definition> that is not contained in an <SQL-client module definition>, then let *DP* be the SQL-path of that <schema definition>.
- D) Otherwise, *UDTN* is contained in an <SQL-client module definition>; let *DP* be the SQL-path of that <SQL-client module definition>.

- 2) Let *N* be the number of <schema name>s in *DP*. Let S_i , $1 \text{ (one)} \leq i \leq N$, be the *i*-th <schema name> in *DP*.
- 3) Let the *set of subject types* be the set containing every user-defined type *T* in the schema identified by some S_i , $1 \text{ (one)} \leq i \leq N$, such that the <qualified identifier> of *T* is equivalent to *QI*. There shall be at least one type in the set of subject types.
- 4) Let *UDT* be the user-defined type contained in the set of subject types such that there is no other type *UDT2* for which the <schema name> of the schema that includes the user-defined type descriptor of *UDT2* precedes in *DP* the <schema name> identifying the schema that includes the user-defined type descriptor of *UDT*. *UDTN* identifies *UDT*.
- 5) The implicit <schema name> of *UDTN* is the <schema name> of the schema that includes the user-defined type descriptor of *UDT*.

b) If *UDTN* is simply contained in <schema-resolved user-defined type name>, then

Case:

- i) If *UDTN* is contained, without an intervening <schema definition> or <SQL-server module definition>, in a <preparable statement> that is prepared in the current SQL-session by an <execute immediate statement> or by a <prepare statement> or in a <direct SQL statement> that is invoked directly, then the implicit <schema name> of *UDTN* is the default <unqualified schema name> of the current SQL-session.
- ii) If *UDTN* is contained in an <SQL-server module definition> without in intervening <schema definition>, then the implicit <schema name> of *UDTN* is the <schema name> that is specified or implicit in <SQL-server module definition>.
- iii) If *UDTN* is contained in a <schema definition> that is not contained in an <SQL-client module definition>, then the implicit <schema name> of *UDTN* is the <schema name> that is specified or implicit in <schema definition>.

- iv) Otherwise, *UDTN* is contained in an <SQL-client module definition>; the implicit <schema name> of *UDTN* is the <schema name> that is specified or implicit in <SQL-client module definition>.

Access Rules

No additional Access Rules.

General Rules

- 1) An <SQL-server module name> identifies an SQL-server module.
- 2) An <SQL variable name> identifies an SQL variable.
- 3) A <condition name> identifies an exception condition or a completion condition and optionally a corresponding SQLSTATE value.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

6 Scalar expressions

This Clause modifies Clause 6, "Scalar expressions", in ISO/IEC 9075-2.

6.1 <value specification> and <target specification>

This Subclause modifies Subclause 6.4, "<value specification> and <target specification>", in ISO/IEC 9075-2.

Function

Specify one or more values, host parameters, SQL parameters, dynamic parameters, host variables, or SQL variables.

Format

```

<general value specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL variable reference>

<simple value specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL variable reference>

<target specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL variable reference>

<simple target specification> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL variable reference>

<target array reference> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL variable reference>

```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

6.2 <identifier chain>

This Subclause modifies Subclause 6.6, "<identifier chain>", in ISO/IEC 9075-2.

Function

Disambiguate a <period>-separated chain of identifiers.

Format

No additional Format items.

Syntax Rules

- 1) Insert before SR8) An SQL variable V is said to be *refinable* if the declared type of V is a row type or a structured type.
- 2) Replace introductory paragraph of SR8) For at most one j between 1 and M , PIC_j is called the *basis* of IC , and j is called the *basis length* of IC . The *referent* of the basis is a column C of a table, an SQL parameter SP , or an SQL variable SV . The basis, basis length, basis scope and basis referent of IC are determined as follows:
- 3) Replace SR8)a)ii) Otherwise, IC shall be contained within the scope of one or more range variables whose associated tables include a column whose <column name> is equivalent to I_1 or within the scope of a <routine name> whose associated <SQL parameter declaration list> includes an SQL parameter whose <SQL parameter name> is equivalent to I_1 or within the scope of one or more <beginning label>s whose associated <local declaration list> includes an SQL variable whose <identifier> is equivalent to I_1 . Let the phrase *possible scope tags* denote those range variables, <routine name>s, and <beginning label>s.
- 4) Insert after SR8)a)ii)1)B) If $IPST$ is a <beginning label>, then let SV be the SQL variable whose <SQL variable name> is equivalent to I_1 . PIC_1 is the basis of IC , the basis length is 1 (one), the basis scope is the scope of SP , and the basis referent is SV .
- 5) Insert before SR8)b)iv) If IC is contained in the scope of a <beginning label> whose associated <local declaration list> includes an SQL variable SV whose <SQL variable name> is equivalent to I_1 , then PIC_1 is a candidate basis of IC , the scope of PIC_1 is the scope of SV , and the referent of PIC_1 is SV .
- 6) Insert before SR8)b)iv) If $N = 2$ and PIC_1 is equivalent to a <beginning label> BL whose scope contains IC and whose associated <local declaration list> includes an SQL variable SV whose <SQL variable name> is equivalent to I_2 , then PIC_2 is a candidate basis of IC , the scope of PIC_2 is the scope of SV , and the referent of PIC_2 is SV .
- 7) Insert before SR8)b)iv) If $N > 2$ and PIC_1 is equivalent to a <beginning label> BL whose scope contains IC and whose associated <local declaration list> includes a refinable SQL variable SV whose <SQL variable name> is equivalent to I_2 , then PIC_2 is a candidate basis of IC , the scope of PIC_2 is the scope of SV , and the referent of PIC_2 is SV .
- 8) Replace SR10) If $BL < N$, then let TIC be the <value expression primary>:

$$(PIC_{BL}) \langle \text{period} \rangle I_{BL+1} \langle \text{period} \rangle \dots \langle \text{period} \rangle I_N$$

The Syntax Rules of Subclause 6.25, "<value expression>", are applied to *TIC*, yielding a column reference, an SQL parameter reference, or an SQL variable reference, and (*N-BL*) <field reference>s, <method invocation>s, <modified field reference>s, and/or <mutator reference>s.

NOTE 3 – In this transformation, (*PIC_{BL}*) is interpreted as a <value expression primary> of the form <left paren> <value expression> <right paren>. *PIC_{BL}* is a <value expression> that is a <value expression primary> that is an <unsigned value specification> that is either a <column reference> or an <SQL parameter reference>. The identifiers *I_{BL+1}*, . . . , *I_N* are parsed using the Syntax Rules of <field reference> and <method invocation>. Alternatively, on the left-hand side of an <assignment statement>, (*PIC_{BL}*) is interpreted as "<left paren> <target specification> <right paren>", and the identifiers *I_{BL+1}*, . . . , *I_N* are parsed using the Syntax Rules of <modified field reference> and <mutator reference>.

- 9) Insert after SR13) A <basic identifier chain> whose basis referent is an SQL variable is an *SQL variable reference*.

Access Rules

None.

General Rules

- 1) Insert this GR If *BIC* is an SQL variable reference, then *BIC* references the SQL variable *SV* of a given execution of the <compound statement> whose <local declaration list> contains the <SQL variable declaration> that declares *SV*.

Conformance Rules

- 1) Without Feature P005, "Qualified SQL variable references", conforming SQL language shall not contain an SQL variable reference whose first <identifier> is the <beginning label> of a <compound statement>.

6.3 <SQL variable reference>

6.3 <SQL variable reference>

Function

Reference an SQL variable.

Format

```
<SQL variable reference> ::=  
    <basic identifier chain>
```

Syntax Rules

- 1) An <SQL variable reference> shall be a <basic identifier chain> that is an SQL variable reference.

Access Rules

None.

General Rules

None.

7 Query expressions

This Clause modifies Clause 7, "Query expressions", in ISO/IEC 9075-2.

7.1 <query specification>

This Subclause modifies Subclause 7.12, "<query specification>", in ISO/IEC 9075-2.

Function

Specify a table derived from the result of a <table expression>.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR7)f)i) If IC is contained in the scope of a <beginning label> whose associated <local declaration list> includes an SQL variable SV whose <SQL variable name> is equivalent to I_1 , then PIC_1 is a candidate basis of IC and the scope of PIC_1 is the scope of SV .
- 2) Insert after SR7)f)i) If $N = 2$ and PIC_1 is equivalent to a <beginning label> BL whose scope contains IC and whose associated <local declaration list> includes an SQL variable SV of row type whose <SQL variable name> is equivalent to I_2 , then PIC_2 is a candidate basis of IC , the scope of PIC_2 is the scope of SV , and the referent of PIC_2 is SV .
- 3) Insert after SR7)f)i) If $N > 2$ and PIC_1 is equivalent to a <beginning label> BL whose scope contains IC and whose associated <local declaration list> includes a refinable SQL variable SV whose <SQL variable name> is equivalent to I_2 , then PIC_2 is a candidate basis of IC , the scope of PIC_2 is the scope of SV , and the referent of PIC_2 is SV .
- 4) Insert after SR18)a)iv) An SQL variable.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

Conformance Rules

- 1) Without Feature P005, "Qualified SQL variable references", conforming SQL language shall not contain an <asterisked identifier chain> whose first <identifier> is the <beginning label> of a <compound statement>.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

8 Additional common elements

This Clause modifies Clause 10, "Additional common elements", in ISO/IEC 9075-2.

8.1 <routine invocation>

This Subclause modifies Subclause 10.4, "<routine invocation>", in ISO/IEC 9075-2.

Function

Invoke an SQL-invoked routine.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR5) An SQL-invoked routine *R* is an *executable routine* if and only if *R* is a possibly candidate routine and

Case:

- a) If *RI* is contained in an <SQL schema statement>, then

Case:

- i) If *RI* is contained in an <SQL-server module definition> *M*, then the applicable privileges for the <authorization identifier> that owns the containing schema include EXECUTE on *M*.
- ii) Otherwise, the applicable privileges for the <authorization identifier> that owns the containing schema include EXECUTE on *R*.

- b) Otherwise,

Case:

- i) If *RI* is contained in an <SQL-server module definition> *M*, then the current privileges include EXECUTE on *M*.
- ii) Otherwise, the current privileges include EXECUTE on *R*.

NOTE 4 – “applicable privileges” and “current privileges” are defined in Subclause 12.3, "<privileges>", in ISO/IEC 9075-2.

- 2) Insert before SR7(b)i)1)C)l) If *RI* is contained in an <SQL-server module definition>, then let *DP* be the SQL-path of that <SQL-server module definition>.
- 3) Replace SR7(b)i)1)C)l) If *RI* is contained in a <schema definition> without an intervening <SQL-server module definition>, then let *DP* be the SQL-path of that <schema definition>.

8.1 <routine invocation>

- 4) Insert before SR8)b)i)1)C)l) If *RI* is contained in an <SQL-server module definition>, then let *DP* be the SQL-path of that <SQL-server module definition>.
- 5) Replace SR8)b)i)1)C)l) If *RI* is contained in a <schema definition> without an intervening <SQL-server module definition>, then let *DP* be the SQL-path of that <schema definition>.
- 6) Replace SR8)c)i)4)B) If A_i is either an <SQL variable name>, the <SQL parameter name> of an SQL parameter of an SQL-invoked routine, or a <target array element specification>, then P_i shall be assignable to A_i , according to the Syntax Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9075-2, with A_i and P_i as *TARGET* and *VALUE*, respectively.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR6)d)i)
NOTE 5 – The identities of declared local temporary tables that are defined in <SQL-server module>s are not removed.
- 2) Replace the introductory paragraph of GR10)b)ii) If TS_i is either an <SQL variable name>, the <SQL parameter name> of an SQL parameter of an SQL-invoked routine, or a <target array element specification>, then

8.2 <sqlstate value>

Function

Specify an SQLSTATE value.

Format

```
<sqlstate value> ::=  
    SQLSTATE [ VALUE ] <character string literal>
```

Syntax Rules

- 1) Let L be the <character string literal> contained in <sqlstate value>.
- 2) The implicit or explicit character set of L shall be the implementation-defined character set in which SQLSTATE parameter values are returned.
- 3) Let V be the character string that is the value of

```
    TRIM ( BOTH ' ' FROM  $L$  )
```
- 4) V shall comprise either:
 - a) Five characters of which the first two have the form of a standard-defined class value and the last three have the form of a standard-defined subclass value.
 - b) Five characters of which the first two have the form of a standard-defined class value and the last three have the form of an implementation-defined subclass value.
 - c) Five characters of which the first two have the form of an implementation-defined class value and the last three have the form of either a standard-defined subclass value or an implementation-defined subclass value.
- 5) V shall not be the SQLSTATE value for the condition *successful completion*.
- 6) The SQLSTATE value defined by the <sqlstate value> is V .

Access Rules

None.

General Rules

None.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

9 Schema definition and manipulation

This Clause modifies Clause 11, "Schema definition and manipulation", in ISO/IEC 9075-2.

9.1 <schema definition>

This Subclause modifies Subclause 11.1, "<schema definition>", in ISO/IEC 9075-2.

Function

Define a schema.

Format

```
<schema element> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <SQL-server module definition>
```

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

9.2 <drop schema statement>

This Subclause modifies Subclause 11.2, "<drop schema statement>", in ISO/IEC 9075-2.

Function

Destroy a schema.

Format

No additional Format items.

Syntax Rules

- 1) Insert this SR If RESTRICT is specified, then *S* shall not include any SQL-server modules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert before GR8 For every SQL-server module *M* contained in *S*, let *MN* be the <SQL-server module name> of *M*. For every *M*, the following <drop module statement> is effectively executed:

```
DROP MODULE MN CASCADE
```

- 2) Replace GR11 Let *R* be any SQL-invoked routine whose routine descriptor contains the <schema name> of *S* in the <SQL routine body>.

Case:

- a) If *R* is included in an SQL-server module *M*, then let *MN* be the <SQL-server module name> of *M*. The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

- b) Otherwise, let *SN* be the <specific name> of *R*. The following <drop routine statement> is effectively executed without further Access Rule checking:

```
DROP SPECIFIC ROUTINE SN CASCADE
```

- 3) Insert after GR11 Let *SSM* be any SQL-server module whose module descriptor includes the <schema name> of *S* and let *MN* be the <SQL-server module name> of *SSM*. The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

9.3 <default clause>

This Subclause modifies Subclause 11.5, "<default clause>", in ISO/IEC 9075-2.

Function

Specify the default for a column, domain, or SQL variable.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR1 The subject data type of a <default clause> is the data type specified in the descriptor identified by the containing <column definition>, <domain definition>, <attribute definition>, <alter column definition>, or <alter domain statement>, or that defined by the <data type> specified in the containing <SQL variable declaration>.

Access Rules

No additional Access Rules.

General Rules

None.

9.4 <drop column scope clause>

This Subclause modifies Subclause 11.16, "<drop column scope clause>", in ISO/IEC 9075-2.

Function

Drop the scope from an existing column of data type REF in a base table.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR3)d The module descriptor of any SQL-server module.

Access Rules

None.

General Rules

- 1) Replace GR1 For every SQL-invoked routine *R* whose routine descriptor includes a <SQL routine body> that contains an impacted dereference operation,

Case:

- a) If *R* is included in an SQL-server module *M*, then let *MN* be the <SQL-server module name> of *M*. The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

- b) Otherwise, let *SN* be the <specific name> of *R*. The following <drop routine statement> is effectively executed for every *R* without further Access Rule checking:

```
DROP SPECIFIC ROUTINE SN CASCADE
```

- 2) Insert after GR4 Let *SSM* be any SQL-server module whose module descriptor includes an impacted dereference operation, and let *MN* be the <SQL-server module name> of *SSM*. The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

9.5 <drop column definition>

This Subclause modifies Subclause 11.18, "<drop column definition>", in ISO/IEC 9075-2.

Function

Destroy a column.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR5 If RESTRICT is specified, then *C* shall not be referenced in any of the following:
 - a) The <query expression> of any view descriptor.
 - b) The <search condition> of any constraint descriptor other than a table constraint descriptor that contains references to no other column and that is included in the table descriptor of *T*.
 - c) The <SQL routine body> of any routine descriptor.
 - d) Either an explicit trigger column list or a triggered action column set of any trigger descriptor.
 - e) The module descriptor of any SQL-server module.

NOTE 6 – A <drop column definition> that does not specify CASCADE will fail if there are any references to that column resulting from the use of CORRESPONDING, NATURAL, SELECT * (except where contained in an exists predicate), or REFERENCES without a <reference column list> in its <referenced table and columns>.

NOTE 7 – If CASCADE is specified, then any such dependent object will be dropped by the execution of the <revoke statement> specified in the General Rules of this Subclause.

NOTE 8 – *CN* may be contained in an implicit trigger column list of a trigger descriptor.

Access Rules

No additional Access Rules.

General Rules

- 2 Rules deleted.

None.

9.6 <drop table constraint definition>

9.6 <drop table constraint definition>

This Subclause modifies Subclause 11.20, "<drop table constraint definition>", in ISO/IEC 9075-2.

Function

Destroy a constraint on a table.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR2 Let R be any SQL-invoked routine whose routine descriptor contains the <constraint name> of TC in the <SQL routine body>.

Case:

- a) If R is included in an SQL-server module M , then let MN be the <SQL-server module name> of M . The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE  $MN$  CASCADE
```

- b) Otherwise, let SN be the <specific name> of R . The following <drop routine statement> is effectively executed without further Access Rule checking:

```
DROP SPECIFIC ROUTINE  $SN$  CASCADE
```

9.7 <drop table statement>

This Subclause modifies Subclause 11.21, "<drop table statement>", in ISO/IEC 9075-2.

Function

Destroy a table.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR6 If RESTRICT is specified, then *T* shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 2 Rules deleted.

None.

9.8 <view definition>

This Subclause modifies Subclause 11.22, "<view definition>", in ISO/IEC 9075-2.

Function

Define a viewed table.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR2)

NOTE 9 – <SQL variable name> is also excluded because of the scoping rules for <SQL variable name>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

9.9 <drop view statement>

This Subclause modifies Subclause 11.23, "<drop view statement>", in ISO/IEC 9075-2.

Function

Destroy a view.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR4 If RESTRICT is specified, then *V* shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 2 Rules deleted.

None.

9.10 <drop domain statement>

This Subclause modifies Subclause 11.30, "<drop domain statement>", in ISO/IEC 9075-2.

Function

Destroy a domain.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR2 If RESTRICT is specified, then *D* shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 1 Rule deleted.

None.

9.11 <drop character set statement>

This Subclause modifies Subclause 11.32, "<drop character set statement>", in ISO/IEC 9075-2.

Function

Destroy a character set.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR4 C shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 2 Rules deleted.

None.

9.12 <drop collation statement>

This Subclause modifies Subclause 11.34, "<drop collation statement>", in ISO/IEC 9075-2.

Function

Destroy a collating sequence.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR 4) If RESTRICT is specified, then *C* shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 2 Rules deleted.

None.

9.13 <drop transliteration statement>

This Subclause modifies Subclause 11.36, "<drop transliteration statement>", in ISO/IEC 9075-2.

Function

Destroy a character transliteration.

Format

No additional Format items.

Syntax Rules

- 1) Insert after GR 4) If RESTRICT is specified, then *C* shall not be referenced in the module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 1 Rule deleted.

None.

9.14 <assertion definition>

This Subclause modifies Subclause 11.37, "<assertion definition>", in ISO/IEC 9075-2.

Function

Specify an integrity constraint by means of an assertion and specify the initial default time for checking the assertion.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR4)

NOTE 10 – <SQL variable name> is also excluded because of the scoping rules for <SQL variable name>.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

9.15 <drop assertion statement>

This Subclause modifies Subclause 11.38, "<drop assertion statement>", in ISO/IEC 9075-2.

Function

Destroy an assertion.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR1 Let R be any SQL-invoked routine whose routine descriptor contains the <constraint name> of A in the <SQL routine body>.

Case:

- a) If R is included in an SQL-server module M , then let MN be the <SQL-server module name> of M . The following <drop module statement> is effectively executed without further Access Rule checking:

DROP MODULE MN CASCADE

- b) Otherwise, let SN be the <specific name> of R . The following <drop routine statement> is effectively executed without further Access Rule checking:

DROP SPECIFIC ROUTINE SN CASCADE

9.16 <trigger definition>

9.16 <trigger definition>

This Subclause modifies Subclause 11.39, "<trigger definition>", in ISO/IEC 9075-2.

Function

Defined triggered SQL-statements.

Format

```
<triggered SQL statement> ::=  
    <SQL procedure statement>
```

NOTE 11 – The preceding production defining <triggered SQL statement> completely supersedes the definition in ISO/IEC 9075-2.

Syntax Rules

- 1) Insert this SR If <SQL procedure statement> simply contains a <compound statement> CS, then CS shall specify ATOMIC.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

9.17 <drop user-defined ordering statement>

This Subclause modifies Subclause 11.56, "<drop user-defined ordering statement>", in ISO/IEC 9075-2.

Function

Destroy a user-defined ordering method.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR4)d) The module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR1) Let R be any SQL-invoked routine that contains P in its <SQL routine body>.
 - a) If R is included in an SQL-server module M with no intervening <schema definition>, then let MN be the <SQL-server module name> of M . The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```
 - b) Otherwise, let SN be the specific name of R . The following <drop routine statement> is effectively executed without further Access Rule checking:

```
DROP SPECIFIC ROUTINE SN CASCADE
```
- 2) Insert after GR6) Let SSM be any SQL-server module whose module descriptor contains P and let MN be the <SQL-server module name> of SSM . The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

9.18 <SQL-server module definition>

Function

Define an SQL-server module.

Format

```
<SQL-server module definition> ::=
    CREATE MODULE <SQL-server module name>
        [ <SQL-server module character set specification> ]
        [ <SQL-server module schema clause> ]
        [ <SQL-server module path specification> ]
        [ <temporary table declaration>... ]
        <SQL-server module contents>...
    END MODULE
```

```
<SQL-server module character set specification> ::=
    NAMES ARE <character set specification>
```

```
<SQL-server module schema clause> ::=
    SCHEMA <default schema name>
```

```
<default schema name> ::=
    <schema name>
```

```
<SQL-server module path specification> ::=
    <path specification>
```

```
<SQL-server module contents> ::=
    <SQL-invoked routine> <semicolon>
```

Syntax Rules

- 1) If an <SQL-server module definition> is contained in a <schema definition> *SD* and the <SQL-server module name> of the <SQL-server module definition> contains a <schema name>, then that <schema name> shall be equivalent to the specified or implicit <schema name> of *SD*.
- 2) The schema identified by the explicit or implicit <schema name> of the <SQL-server module name> shall not include a module descriptor whose <SQL-server module name> is equivalent to the <SQL-server module name> of the containing <SQL-server module definition>.
- 3) The SQL-invoked routine specified by <SQL-invoked routine> shall not be a schema-level routine.
NOTE 12 – “Schema-level routine” is defined in Subclause 11.50, “<SQL-invoked routine>”, in ISO/IEC 9075-2.
- 4) If <SQL-server module path specification> is not specified, then an <SQL-server module path specification> containing an implementation-defined <schema name list> that includes the explicit or implicit <schema name> of the <SQL-server module name> is implicit.
- 5) The explicit or implicit <catalog name> of each <schema name> contained in the <schema name list> of the <SQL-server module path specification> shall be equivalent to the <catalog name> of the explicit or implicit <schema name> of the <SQL-server module name>.

- 6) The <schema name list> of the explicit or implicit <SQL-server module path specification> is used as the SQL-path of the SQL-server module. The SQL-path is used to effectively qualify unqualified <routine name>s that are immediately contained in <routine invocation>s that are contained in the <SQL-server module definition>.
- 7) If <SQL-server module schema clause> is not specified, then an <SQL-server module schema clause> containing the <default schema name> that is equivalent to the explicit or implicit <schema name> of the <SQL-server module name> is implicit.
- 8) If <SQL-server module character set specification> is not specified, then an <SQL-server module character set specification> containing the <character set specification> that is equivalent to the <schema character set specification> of the schema identified by the explicit or implicit <schema name> of the <SQL-server module name> is implicit.
- 9) The explicit or implicit <SQL-server module character set specification> is the character set in which the SQL-server module is represented. If the SQL-server module is actually represented in a different character set, then the effects are implementation-dependent.

Access Rules

- 1) If an <SQL-server module definition> is contained in an <SQL-client module definition> with no intervening <schema definition>, then the enabled authorization identifiers shall include the <authorization identifier> that owns the schema identified by the implicit or explicit <schema name> of the <SQL-server module name>.

General Rules

- 1) An <SQL-server module definition> defines an SQL-server module.
- 2) A privilege descriptor is created that defines the EXECUTE privilege on the SQL-server module to the <authorization identifier> that owns the schema identified by the explicit or implicit <schema name> of the <SQL-server module name>. The grantor for the privilege descriptor is set to the special grantor value “_SYSTEM”. This privilege is grantable if and only if all of the privileges necessary for the <authorization identifier> to successfully execute the <SQL procedure statement> contained in the <routine body> of every <SQL-invoked routine> contained in the <SQL-server module definition> are grantable.

NOTE 13 – The necessary privileges include the EXECUTE privilege on every subject routine of every <routine invocation> contained in the <SQL procedure statement>.

- 3) An SQL-server module descriptor is created that describes the SQL-server module being defined. The SQL-server module descriptor includes:
 - a) The SQL-server module name specified by the <SQL-server module name>.
 - b) The descriptor of the character set specified by the <SQL-server module character set specification>.
 - c) The default schema name specified by the <SQL-server module schema clause>.
 - d) The SQL-server module authorization identifier that corresponds to the authorization identifier that owns the schema identified by the explicit or implicit <schema name> of the <SQL-server module name>.
 - e) The list of schema names contained in the <SQL-server module path specification>.
 - f) The descriptor of every local temporary table declared in the SQL-server module.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

9.18 <SQL-server module definition>

- g) The descriptor of every SQL-invoked routine contained in the SQL-server module.
- h) The text of the <SQL-server module definition>.

9.19 <drop module statement>

Function

Destroy an SQL-server module.

Format

```
<drop module statement> ::=  
    DROP MODULE <SQL-server module name> <drop behavior>
```

Syntax Rules

- 1) Let *MN* be the <SQL-server module name> and let *M* be the SQL-server module identified by *MN*.
- 2) *M* shall be an SQL-server module.
- 3) If RESTRICT is specified, then the descriptor of *M* shall not include the descriptor of an SQL-invoked routine that is included in the subject routines of a <routine invocation> that is contained in any of the following:
 - a) The <SQL routine body> of any routine descriptor not included in the module descriptor of *M*.
 - b) The <query expression> of any view descriptor.
 - c) The <search condition> of any constraint descriptor or assertion descriptor.
 - d) Any trigger descriptor.
 - e) The module descriptor of any SQL-server module other than *M*.

Access Rules

- 1) The enabled authorization identifiers shall include the <authorization identifier> that owns the schema identified by the <schema name> of *M*.

General Rules

- 1) Let *A* be the current authorization identifier. The following <revoke statement> is effectively executed with a current authorization identifier of “_SYSTEM” and without further Access Rule checking:

```
REVOKE EXECUTE ON MODULE MN FROM A CASCADE
```

- 2) The descriptor of *M* is destroyed.

9.20 <drop data type statement>

This Subclause modifies Subclause 11.49, "<drop data type statement>", in ISO/IEC 9075-2.

Function

Destroy a user-defined type.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR4)f)v) The module descriptor of any SQL-server module.
- 2) Insert after SR4)h)i)4) The module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

9.21 <SQL-invoked routine>

This Subclause modifies Subclause 11.50, "<SQL-invoked routine>", in ISO/IEC 9075-2.

Function

Define an SQL-invoked routine.

Format

```
<SQL-invoked routine> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | <module routine>  
  
<module routine> ::=  
    <module procedure>  
    | <module function>  
  
<module procedure> ::=  
    [ DECLARE ] <SQL-invoked procedure>  
  
<module function> ::=  
    [ DECLARE ] <SQL-invoked function>
```

Syntax Rules

- 1) Replace SR6)h) Case:
 - a) If an <SQL-invoked routine> is contained in an <SQL-server module definition>, and <language clause> is not specified, then a <language clause> that is equivalent to the <language clause> of the <SQL-server module definition> is implicit.
 - b) If an <SQL-invoked routine> is not contained in an <SQL-server module definition> and <language clause> is not specified, then LANGUAGE SQL is implicit.
- 2) Replace SR6)r) If <SQL-invoked routine> is contained in a <schema definition> without an intervening <SQL-server module definition> and *RN* contains a <schema name> *SN*, then *SN* shall be equivalent to the specified or implicit <schema name> of the containing <schema definition>. Let *S* be the SQL-schema identified by *SN*.
- 3) Insert after SR6)r) If <SQL-invoked routine> is contained in an <SQL-server module definition> and if *RN* contains a <schema name> *SN*, then *SN* shall be equivalent to the specified <schema name> of the containing <SQL-server module definition>. Let *S* be the SQL-schema identified by *SN*.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR3)z) If the SQL-invoked routine is a schema-level routine, then the schema name of the schema that includes the SQL-invoked routine; otherwise, the SQL-server module name of the SQL-server module that includes the SQL-invoked routine and the schema name of the schema that includes that SQL-server module.

9.22 <drop routine statement>

This Subclause modifies Subclause 11.52, "<drop routine statement>", in ISO/IEC 9075-2.

Function

Destroy an SQL-invoked routine.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR5)a)iv) The module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

9.23 <drop user-defined cast statement>

9.23 <drop user-defined cast statement>

This Subclause modifies Subclause 11.54, "<drop user-defined cast statement>", in ISO/IEC 9075-2.

Function

Destroy a user-defined cast.

Format

No additional Format items.

Syntax Rules

- 1) Insert after SR7)d The module descriptor of any SQL-server module.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

10 Access control

This Clause modifies Clause 12, "Access control", in ISO/IEC 9075-2.

10.1 <grant statement>

This Subclause modifies Subclause 12.1, "<grant statement>", in ISO/IEC 9075-2.

Function

Define privileges.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert this GR For every involved grantee *G* and for every SQL-server module *M1* owned by *G*, if the applicable privileges for *G* contain all of the privileges necessary to successfully execute every <SQL procedure statement> contained in the <routine body> of every SQL-invoked routine contained in *M1* WITH GRANT OPTION, then for every privilege descriptor with a <privileges> EXECUTE, a <grantor> of “_SYSTEM”, <object> of *M1*, and <grantee> *G* that is not grantable, the following <grant statement> is executed with a current user identifier of “_SYSTEM” and without further Access Rule checking:

GRANT EXECUTE ON *M1* TO *G* WITH GRANT OPTION.

NOTE 14 – The privileges necessary include the EXECUTE privilege on every subject routine of every <routine invocation> contained in those <SQL procedure statement>s.

10.2 <privileges>

10.2 <privileges>

This Subclause modifies Subclause 12.3, "<privileges>", in ISO/IEC 9075-2.

Function

Specify privileges.

Format

```
<object name> ::=  
    !! All alternatives from ISO/IEC 9075-2  
    | MODULE <module name>
```

Syntax Rules

- 1) Replace SR7 If the object identified by <object name> of the <grant statement> or <revoke statement> is an SQL-invoked routine or an SQL-server module, then <privileges> shall specify EXECUTE; otherwise, EXECUTE shall not be specified.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

10.3 <revoke statement>

This Subclause modifies Subclause 12.7, "<revoke statement>", in ISO/IEC 9075-2.

Function

Destroy privileges.

Format

No additional Format items.

Syntax Rules

- 1) [Insert after SR20)e] EXECUTE privilege on every SQL-server module that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is generally contained in the <query expression> of *V*.
- 2) [Insert after SR22)e] EXECUTE privilege on every SQL-server modules that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is generally contained in any <search condition> of *TC*.
- 3) [Insert after SR23)e] EXECUTE privilege on every SQL-server module that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is generally contained in any <search condition> of *AX*.
- 4) [Insert after SR25)e] EXECUTE privilege on every SQL-server module that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is generally contained in any <search condition> of *DC*.
- 5) [Insert after SR34)a] EXECUTE privilege on every SQL-server module that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is contained in the <routine body> of *RD*.
- 6) [Insert this SR] Let *SSM* be any SQL-server module descriptor of an SQL-server module included in *S1*. *SSM* is said to be *abandoned* if the revoke destruction action would result in *A1* no longer having of all of the following:
 - a) EXECUTE privilege on every schema-level routine that is among the subject routines of a <routine invocation> that is contained in the <routine body> of any SQL-invoked routine included in *SSM*.
 - b) EXECUTE privilege on every SQL-server module that includes one or more SQL-invoked routines that are among the subject routines of a <routine invocation> that is contained in the <SQL routine body> of any SQL-invoked routine included in *SSM*.
 - c) SELECT privilege on at least one column of each table identified by a <table reference> contained in a <query expression> simply contained in a <cursor specification>, an <insert statement>, or a <merge statement> contained in the <routine body> of any SQL-invoked routine with a security characteristic of *DEFINER* included in *SSM*.

10.3 <revoke statement>

- d) SELECT privilege on at least one column of each table identified by a <table reference> contained in a <table expression> or <select list> immediately contained in a <select statement: single row> contained in the <routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- e) SELECT privilege on at least one column of each table identified by a <table reference> contained in a <search condition> contained in a <delete statement: positioned>, an <update statement: searched>, or a <merge statement> contained in the <routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- f) SELECT privilege on at least one column of each table identified by a <table reference> contained in a <value expression> simply contained in an <update source> or an <assigned row> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- g) SELECT privilege on at least one column identified by a <column reference> contained in a <search condition> contained in a <delete statement: searched>, an <update statement: searched>, or a <merge statement> contained in the <SQL routine body> of any SQL-invoked routine included in *SSM*.
- h) SELECT privilege on at least one column identified by a <column reference> contained in a <value expression> simply contained in an <update source> or an <assigned row> contained in the SQL routine body of any SQL-invoked routine included in *SSM*.
- i) INSERT privilege on every column
Case:
 - i) Identified by a <column name> contained in the <insert column list> of an <insert statement> contained in the <routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
 - ii) Of the table identified by the <table name> immediately contained in an <insert statement> that does not contain an <insert column list> and that is contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
 - iii) Of the table identified by the <target table> immediately contained in an <merge statement> that contains a <merge specification> and that does not contain an <insert column list> and that is contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- j) UPDATE privilege on every column whose name is contained in an <object column> contained in either an <update statement: positioned>, an <update statement: searched>, or a <merge statement> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- k) DELETE privilege on every table whose name is contained in a <table name> immediately contained in either a <delete statement: positioned> or a <delete statement: searched> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- l) USAGE privilege on every domain, every collation, every character set, and every transliteration whose name is contained in the <routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.

- m) USAGE privilege on every user-defined type *UDT* such that there is a <data type> contained in the <routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM* that is usage-dependent on *UDT*.
- n) The table/method privilege on every table *T1* and every method *M* such that there is a <method reference> *MR* contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM* such that *T1* is in the scope of the <value expression primary> of *MR* and *M* is the subject routine of *MR*.
- o) SELECT privilege WITH HIERARCHY OPTION on at least one supertable of the scoped table of any <reference resolution> that is contained in any <query expression> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- p) SELECT privilege WITH HIERARCHY OPTION on at least one supertable of the scoped table of any <reference resolution> that is contained in any <table expression> or <select list> immediately contained in a <select statement: single row> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- q) SELECT privilege WITH HIERARCHY OPTION on at least one supertable of the scoped table of any <reference resolution> that is contained in any <search condition> contained in a <delete statement: searched>, an <update statement: searched>, or a <merge statement> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- r) SELECT privilege WITH HIERARCHY OPTION on at least one supertable of the scoped table of any <reference resolution> that is contained in any <value expression> simply contained in an <update source> or an <assigned row> contained in the <SQL routine body> of any SQL-invoked routine with a security characteristic of DEFINER included in *SSM*.
- s) SELECT privilege WITH HIERARCHY OPTION on at least one supertable of every typed table identified by a <table reference> that simply contains an <only spec> and that is contained in the <SQL routine body> of *RD*.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR16) For every abandoned SQL-server module descriptor *MD*, let *M* be the SQL-server module whose descriptor is *MD*. Let *MN* be the <SQL-server module name> of *M*. The following <drop module statement> is effectively executed without further Access Rule checking:

```
DROP MODULE MN CASCADE
```

SC32 N00745 = WG3:VIE-006 = H2-2002-008

11 SQL-client modules

This Clause modifies Clause 13, "SQL-client modules", in ISO/IEC 9075-2.

11.1 Calls to an <externally-invoked procedure>

This Subclause modifies Subclause 13.4, "Calls to an <externally-invoked procedure>", in ISO/IEC 9075-2.

Function

Define the call to an <externally-invoked procedure> by an SQL-agent.

Syntax Rules

1) Insert into SR2)e

```

CASE_NOT_FOUND_FOR_CASE_STATEMENT_NO_SUBCLASS:
    constant SQLSTATE_TYPE := "20000";
DATA_EXCEPTION_NULL_VALUE_IN_FIELD_REFERENCE:
    constant SQLSTATE_TYPE := "2202A";
DIAGNOSTICS_EXCEPTION_STACKED_DIAGNOSTICS_ACCESSED_WITHOUT_ACTIVE_HANDLER:
    constant SQLSTATE_TYPE := "0Z002";
RESIGNAL_WHEN_HANDLER_NOT_ACTIVE_NO_SUBCLASS:
    constant SQLSTATE_TYPE := "0K000";
UNHANDLED_USER_DEFINED_EXCEPTION_NO_SUBCLASS:
    constant SQLSTATE_TYPE := "45000";

```

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

11.2 <SQL procedure statement>

This Subclause modifies Subclause 13.5, "<SQL procedure statement>", in ISO/IEC 9075-2.

Function

Define all of the SQL-statements that are <SQL procedure statement>s.

Format

```
<SQL schema definition statement> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <SQL-server module definition>

<SQL schema manipulation statement> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <drop module statement>

<SQL control statement> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <assignment statement>
    | <compound statement>
    | <case statement>
    | <if statement>
    | <iterate statement>
    | <leave statement>
    | <loop statement>
    | <while statement>
    | <repeat statement>
    | <for statement>

<SQL diagnostics statement> ::=
    !! All alternatives from ISO/IEC 9075-2
    | <signal statement>
    | <resignal statement>
```

Syntax Rules

- 1) Replace SR 2) An <SQL connection statement> shall not be generally contained in an <SQL control statement>, an <SQL-invoked routine>, or an <SQL-server module definition>.
- 2) Insert after SR 4)d) *S* is a <compound statement> and *S* contains an <SQL variable declaration> that specifies a <default option> that contains a <datetime value function>, CURRENT_USER, CURRENT_ROLE, SESSION_USER, or SYSTEM_USER.
- 3) Insert after SR 4)d) *S* is a <compound statement> and *S* contains an <SQL variable declaration> that specifies a <domain name> and the domain descriptor identified by the <domain name> has a default value that contains a <datetime value function>, CURRENT_USER, CURRENT_ROLE, SESSION_USER, or SYSTEM_USER.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR 4)a)iii)6) If *S* is not a <compound statement>, then the first diagnostics area is emptied.
- 2) Insert before GR 7) Condition handling mode becomes in effect in the SQL-session.
- 3) Insert before GR 7) The General Rules of Subclause 13.2, “<handler declaration>”, are applied.
- 4) Insert after GR 9) Condition handling mode ceases to be in effect in the SQL-session.

Conformance Rules

- 1) Without Feature P001, “Stored modules”, an <SQL procedure statement> shall not be an <SQL server module definition> or a <drop module statement>.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

12 Data manipulation

This Clause modifies Clause 14, "Data manipulation", in ISO/IEC 9075-2.

12.1 <open statement>

This Subclause modifies Subclause 14.2, "<open statement>", in ISO/IEC 9075-2.

Function

Open a cursor.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR1 Let *CN* be the <cursor name> in the <open statement>. *CN* shall be contained within the scope of one or more <cursor name>s that are equivalent to *CN*. If there is more than one such <cursor name>, then the one with the innermost scope is specified. Let *CR* be the cursor specified by *CN*.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

12.2 <fetch statement>

This Subclause modifies Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2.

Function

Position a cursor on a specified row of a table and retrieve values from that row.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR3 Let *CN* be the <cursor name> in the <fetch statement>. *CN* shall be contained within the scope of one or more <cursor name>s that are equivalent to *CN*. If there is more than one such <cursor name>, then the one with the innermost scope is specified. Let *CR* be the cursor specified by *CN*. Let *T* be the table defined by the <cursor specification> of *CR*. Let *DC* be the <declare cursor> denoted by *CN*.
- 2) Replace SR6)a)i If *TS* is an <SQL variable reference> or an <SQL parameter reference>, then the Syntax Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9072-2, apply to *TS* and the row type of table *T* as *TARGET* and *VALUE*, respectively.
- 3) Replace the introductory paragraph of SR6)b)ii For *i* varying from 1 (one) to *NTS*, let *TS1_i* be the *i*-th <target specification> in the <fetch target list> that is either an <SQL variable name>, an <SQL parameter reference>, or a <target array element specification>, and let *CS_i* be the *i*-th column of table *T* that corresponds with the <target specification> in the <fetch target list>.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR7)a)i If *TS* is an <SQL variable reference> or an <SQL parameter reference>, then the General Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9072-2, apply to *TS* and the current row as *TARGET* and *VALUE*, respectively.
- 2) Replace the introductory paragraph of GR7)b)i If *TV* is either an <SQL variable reference>, an <SQL parameter reference>, or a <target array element specification>, then for each <target specification> in the <fetch target list>, let *TV_i* be the *i*-th <target specification> in the <fetch target list> and let *SV_i* denote the *i*-th corresponding value in the current row of *CR*.

12.3 <close statement>

This Subclause modifies Subclause 14.4, "<close statement>", in ISO/IEC 9075-2.

Function

Close a cursor.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR1 Let *CN* be the <cursor name> in the <close statement>. *CN* shall be contained within the scope of one or more <cursor name>s that are equivalent to *CN*. If there is more than one such <cursor name>, then the one with the innermost scope is specified. Let *CR* be the cursor specified by *CN*.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

12.4 <select statement: single row>

This Subclause modifies Subclause 14.5, "<select statement: single row>", in ISO/IEC 9075-2.

Function

Retrieve values from a specified row of a table.

Format

No additional Format items.

Syntax Rules

- 1) Replace the introductory paragraph of SR3) For i varying from 1 (one) to NOE , let TS_i be the i -th <target specification> in the <select target list> that is either an <SQL variable reference>, an <SQL parameter reference>, or a <target array element specification>, and let SL_i be the i -th element of the <select list that corresponds with the <target specification> in the <select target list>.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace the introductory paragraph of GR5) For i varying from 1 (one) to NOE , let TS_i be the i -th <target specification> in the <select target list> that is either an <SQL variable reference>, an <SQL parameter reference>, or a <target array element specification>, and let SL_i denote the corresponding (i -th) value in the row of Q . The assignment of values to targets in the <select target list> is in an implementation-dependent order.

12.5 <delete statement: positioned>

This Subclause modifies Subclause 14.6, "<delete statement: positioned>", in ISO/IEC 9075-2.

Function

Delete a row of a table.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR1 Let *CN* be the <cursor name> in the <delete statement: positioned>. *CN* shall be contained within the scope of one or more <cursor name>s that are equivalent to *CN*. If there is more than one such <cursor name>, then the one with the innermost scope is specified. Let *CR* be the cursor specified by *CN*.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

12.6 <update statement: positioned>

12.6 <update statement: positioned>

This Subclause modifies Subclause 14.10, "<update statement: positioned>", in ISO/IEC 9075-2.

Function

Update a row of a table.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR1 Let *CN* be the <cursor name> in the <update statement: positioned>. *CN* shall be contained within the scope of one or more <cursor name>s that are equivalent to *CN*. If there is more than one such <cursor name>, then the one with the innermost scope is specified. Let *CR* be the cursor specified by *CN*.

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

12.7 <temporary table declaration>

This Subclause modifies Subclause 14.13, "<temporary table declaration>", in ISO/IEC 9075-2.

Function

Replace 1st paragraph Declare a declared local temporary table that will be effectively materialized the first time that any <externally-invoked procedure> in the <SQL-client module definition> that contains, without an intervening <SQL-server module definition>, the <temporary table declaration> is executed or <SQL-invoked routine> in the <SQL-server module definition> that contains the <temporary table declaration> is executed. The scope of the declared local temporary table is all the <externally-invoked procedure>s of that <SQL-client module definition> or <SQL-invoked routine>s of that <SQL-server module definition> executed within the same SQL-session.

Format

No additional Format items.

Syntax Rules

- 1) Replace SR2 Case:
 - a) If a <temporary table declaration> is contained in an <SQL-client module definition> without an intervening <SQL-server module definition>, then *TN* shall not be equivalent to the <table name> of any other <temporary table declaration> contained without an intervening <SQL-server module definition> in the <SQL-client module definition>.
 - b) Otherwise, *TN* shall not be equivalent to the <table name> of any other <temporary table declaration> contained in the <SQL-server module definition>.

Access Rules

No additional Access Rules.

General Rules

- 1) Replace GR1 Case:
 - a) If <temporary table declaration> is contained in an <SQL-client module definition> without an intervening <SQL-server module definition>, then let *U* be the implementation-dependent <schema name> that is effectively derived from the implementation-dependent SQL-session identifier associated with the SQL-session and an implementation-dependent name associated with the SQL-client module that contains the <temporary table declaration>.
 - b) Otherwise, let *U* be the implementation-dependent <schema name> that is effectively derived from the implementation-dependent SQL-session identifier associated with the SQL-session and the name associated of the <SQL-server module definition> that contains the <temporary table declaration>.

12.7 <temporary table declaration>

2) Replace GR3 Case:

- a) If <temporary table declaration> is contained in an <SQL-client module definition> without an intervening <SQL-server module definition>, then the definition of T within the <SQL-client module definition> is effectively equivalent to the definition of a persistent base table $U.T$. Within the SQL-client module, any reference to $MODULE.T$ that is not contained in an <SQL schema statement> is equivalent to a reference to $U.T$.
- b) Otherwise, the definition of T within an <SQL-server module definition> is effectively equivalent to the definition of a persistent base table $U.T$. Within the SQL-server module, any reference to $MODULE.T$ is equivalent to a reference to $U.T$.

13 Control statements

This Clause modifies Clause 15, "Control statements", in ISO/IEC 9075-2.

13.1 <compound statement>

Function

Specify a statement that groups other statements together.

Format

```

<compound statement> ::=
    [ <beginning label> <colon> ]
    BEGIN [ [ NOT ] ATOMIC ]
    [ <local declaration list> ]
    [ <local cursor declaration list> ]
    [ <local handler declaration list> ]
    [ <SQL statement list> ]
    END [ <ending label> ]

<beginning label> ::= <statement label>

<ending label> ::= <statement label>

<statement label> ::= <identifier>

<local declaration list> ::= <terminated local declaration>...

<terminated local declaration> ::= <local declaration> <semicolon>

<local declaration> ::=
    <SQL variable declaration>
    | <condition declaration>

<local cursor declaration list> ::=
    <terminated local cursor declaration>...

<terminated local cursor declaration> ::=
    <declare cursor> <semicolon>

<local handler declaration list> ::=
    <terminated local handler declaration>...

<terminated local handler declaration> ::=
    <handler declaration> <semicolon>

<SQL statement list> ::= <terminated SQL statement>...

<terminated SQL statement> ::=
    <SQL procedure statement> <semicolon>

```

13.1 <compound statement>

Syntax Rules

- 1) Let *CS* be the <compound statement>.
- 2) If *CS* is contained in another <SQL control statement> and *CS* does not specify a <beginning label>, then an implementation-dependent <beginning label> that is not equivalent to any other <statement label> contained in the outermost containing <SQL control statement> is implicit.
- 3) If an <ending label> is specified, then *CS* shall specify a <beginning label> that is equivalent to that <ending label>.
- 4) The scope of the <beginning label> is *CS* excluding every <SQL schema statement> contained in *CS* and every <local handler declaration list> contained in *CS*. <beginning label> shall not be equivalent to any other <beginning label>s contained in *CS* excluding every <SQL schema statement> that is contained in *CS* without an intervening <SQL schema statement> or <handler declaration>.
- 5) If *CS* specifies neither ATOMIC nor NOT ATOMIC, then NOT ATOMIC is implicit.
- 6) If *CS* specifies ATOMIC, then the <SQL statement list> shall not contain either a <commit statement> or a <rollback statement> that does not specify a <savepoint clause>.
- 7) Let *VN* be an <SQL variable name> contained in a <local declaration list>. The *declared local name* of the variable identified by *VN* is *VN*.
- 8) Let *CN* be the <condition name> immediately contained in a <condition declaration> contained in a <local declaration list>. The *declared local name* of the <condition declaration> is *CN*.
- 9) Let *CN* be the <cursor name> immediately contained in a <declare cursor> *DC* contained in a <local cursor declaration list>. The *declared local name* of the cursor declared by *DC* is *CN*.
- 10) No two variables declared in a <local declaration list> shall have equivalent declared local names.
- 11) No two <condition declaration>s contained in a <local declaration list> shall have equivalent declared local names.
- 12) No two cursors declared in a <local cursor declaration list> shall have equivalent declared local names.
- 13) The scope of an <SQL variable name> of an <SQL variable declaration> simply contained in a <local declaration> simply contained in *CS* is the <local cursor declaration list> of *CS*, the <local handler declaration list> *LHDL* of *CS* excluding every <SQL schema statement> contained in *LHDL*, and the <SQL statement list> *SSL* of *CS* excluding every <SQL schema statement> contained in *SSL*.
- 14) The scope of the <condition name> in a <condition declaration> simply contained in a <local declaration> simply contained in *CS* is the <local handler declaration list> *LHDL* of *CS* excluding every <SQL schema statement> contained in *LHDL* and the <SQL statement list> *SSL* of *CS* excluding every <SQL schema statement> contained in *SSL*.
- 15) The scope of the <cursor name> in a <declare cursor> simply contained in a <terminated local cursor declaration> simply contained in *CS* is the <local handler declaration list> *LHDL* of *CS* excluding every <SQL schema statement> contained in *LHDL* and the <SQL statement list> *SSL* of *CS* excluding every <SQL schema statement> contained in *SSL*.

- 16) The scope of a <handler declaration> simply contained in a <local handler declaration list> simply contained in *CS* is the <SQL statement list> *SSL* of *CS* excluding every <SQL schema statement> contained in *SSL*.
- 17) If the <compound statement> simply contains a <handler declaration> that specifies UNDO, then ATOMIC shall be specified.

Access Rules

None.

General Rules

- 1) A new savepoint level is established.
- 2) The SQL variables, cursors, and handlers specified in the <local declaration list>, <local cursor declaration list>, and the <local handler declaration list> of *CS* are created in an implementation-dependent order.
- 3) Let *N* be the number of <SQL procedure statement>s contained in the <SQL statement list> that is immediately contained in *CS* without an intervening <SQL control statement>. For *i* ranging from 1 (one) to *N*:
 - a) Let S_i be the *i*-th such <SQL procedure statement>.
 - b) The General Rules of Subclause 13.5, "<SQL procedure statement>", in ISO/IEC 9075-2, are evaluated with S_i as the *executing statement*.
 - c) If the execution of S_i terminates with exception conditions or completion conditions other than *successful completion*, then:
 - i) The following <resignal statement> is effectively executed without further Syntax Rule checking:

```
RESIGNAL
```
 - ii) If there are unhandled exception conditions at the completion of the execution of a handler (if any), then the execution of *CS* is terminated immediately.
 - 1) For every open cursor *CR* that is declared in the <local declaration list> of *CS*, the following SQL-statement is effectively executed:

```
CLOSE CR
```
 - 2) The SQL variables, cursors, and handlers specified in the <local declaration list>, the <local cursor declaration list>, and the <local handler declaration list> of *CS* are destroyed.
- 4) For every open cursor *CR* that is not a result set cursor that is declared in the <local cursor declaration list> of *CS*, the following SQL-statement is effectively executed:

```
CLOSE CR
```

NOTE 15 – “result set cursor” is defined in Subclause 4.34, "Cursors", in ISO/IEC 9075-2.
- 5) The SQL variables, cursors that are not open result set cursors, and handlers specified in <local declaration list>, the <local cursor declaration list>, and the <local handler declaration list> of *CS* are destroyed.

13.1 <compound statement>

- 6) If *CS* specifies *ATOMIC*, then the current savepoint level is destroyed.

NOTE 16 – Destroying a savepoint level destroys all existing savepoints that are established at that level.

- 7) The <condition name> of every <condition declaration> contained in <local declaration list> ceases to be considered to be defined.

13.2 <handler declaration>

Function

Associate a handler with exception or completion conditions to be handled in a module or compound statement.

Format

```
<handler declaration> ::=
    DECLARE <handler type> HANDLER
    FOR <condition value list>
    <handler action>

<handler type> ::=
    CONTINUE
    | EXIT
    | UNDO

<handler action> ::=
    <SQL procedure statement>

<condition value list> ::=
    <condition value> [ { <comma> <condition value> }... ]

<condition value> ::=
    <sqlstate value>
    | <condition name>
    | SQLEXCEPTION
    | SQLWARNING
    | NOT FOUND
```

Syntax Rules

- 1) Let *HD* be the <handler declaration>.
- 2) A <condition name> *CN* specified in a <condition value> of *HD* shall be defined by some <condition declaration> with a scope that contains *HD*. Let *C* be the condition specified by the innermost such <condition declaration>.
- 3) If a <condition value> specifies SQLEXCEPTION, SQLWARNING, or NOT FOUND, then neither <sqlstate value> nor <condition value> shall be specified.
- 4) No other <handler declaration> with the same scope as *HD* shall contain in its <condition value list> a <condition value> that represents the same condition as a <condition value> contained in the <condition value list> of *HD*.
- 5) The <condition value list> shall not contain the same <condition value> or <sqlstate value> more than once, nor shall it contain both the <condition name> of a condition *C* and an <sqlstate value> that represents the SQLSTATE value associated with *C*.
- 6) SQLEXCEPTION, SQLWARNING, and NOT FOUND correspond to SQLSTATE class values corresponding to categories X, W, and N, respectively, in Subclause 23.1, "SQLSTATE", in ISO/IEC 9075-2.

13.2 <handler declaration>

- 7) If a <condition value> specifies SQLEXCEPTION, SQLWARNING, or NOT FOUND, then the <handler declaration> is a *general <handler declaration>*; otherwise, the <handler declaration> is a *specific <handler declaration>*.
- 8) If there is a general <handler declaration> and a specific <handler declaration> for the same <condition value> in the same scope, then only the specific <handler declaration> is associated with that <condition value>.
- 9) Let *HA* be the <handler action>.
- 10) *HA* is associated with every <condition name> specified in the <condition value list> of *HD* and with every SQLSTATE value specified in every <sqlstate value> specified in the <condition value list> of *HD*.
- 11) If *HA* is associated with a <condition name> and that <condition name> was defined for an SQLSTATE value, then *HA* is also associated with that SQLSTATE value.
- 12) If *HA* is associated with an SQLSTATE class, then it is associated with each SQLSTATE value of that class.

Access Rules

None.

General Rules

- 1) When the handler *H* associated with the conditions specified by *HD* is created, it is the *most appropriate handler* for any condition *CN* raised during execution of any SQL-statements that are in the scope of *HD* that has an SQLSTATE value or condition name that is the same as an SQLSTATE value or condition name associated with this handler, until *H* is destroyed. *CN* has a more appropriate handler if, during the existence of *H*, another handler *AH* is created with a scope containing *CN*, and if *AH* is associated with an SQLSTATE value or condition name that is the same as the SQLSTATE value or condition name of *CN*. *AH* replaces *H* as the most appropriate handler for *CN* until *AH* is destroyed. When *AH* is destroyed, *H* is reinstated as the most appropriate handler for *CN*.
- 2) Let *CS* be the <compound statement> simply containing *HD*.
- 3) When *H* is activated,
Case:
 - a) If *HD* specifies CONTINUE, then:
 - i) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.
 - ii) *HA* is executed.
 - iii) Case:
 - 1) If there is an unhandled condition other than *successful completion* at the completion of *HA*, then:
 - A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area

stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.

B) The following <resignal statement> is effectively executed:

RESIGNAL

2) Otherwise:

A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "POP" as *OPERATION* and the diagnostics area stack as *STACK*.

B) *HA* completes with completion condition *successful completion* and the SQL-session continues as it would have done if execution of the innermost executing statement that raised the condition had completed.

b) If *HD* specifies EXIT, then:

i) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.

ii) *HA* is executed.

iii) For every open cursor *CR* that was declared in *CS* and that is not a result set cursor, the following statement is implicitly executed:

CLOSE *CR*

iv) Case:

1) If there is an unhandled condition other than *successful completion* at the completion of *HA*, then:

A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.

B) The following <resignal statement> is effectively executed:

RESIGNAL

2) Otherwise:

A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "POP" as *OPERATION* and the diagnostics area stack as *STACK*.

B) *HA* completes with completion condition *successful completion* and the SQL-session continues as it would have done if execution of *CS* had completed.

c) If *HD* specifies UNDO, then:

i) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.

13.2 <handler declaration>

ii) All changes made to SQL-data or schemas by the execution of SQL-statements contained in the <SQL statement list> of *CS* and any <SQL procedure statement>s triggered by the execution of any such statements are canceled.

iii) For every open cursor *CR* that was declared in *CS*, the following statement is implicitly executed:

CLOSE *CR*

iv) *HA* is executed.

v) Case:

1) If there is an unhandled condition other than *successful completion* at the completion of *HA*, then:

A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "PUSH" as *OPERATION* and the diagnostics area stack as *STACK*.

B) The following <resignal statement> is effectively executed:

RESIGNAL

2) Otherwise:

A) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "POP" as *OPERATION* and the diagnostics area stack as *STACK*.

B) *HA* completes with completion condition *successful completion* and the SQL-session continues as it would have done if execution of *CS* had completed.

13.3 <condition declaration>

Function

Declare a condition name and an optional corresponding SQLSTATE value.

Format

```
<condition declaration> ::=  
    DECLARE <condition name> CONDITION  
    [ FOR <sqlstate value> ]
```

Syntax Rules

- 1) Let *CD* be the <condition declaration>.
- 2) Let *CN* be the <condition name>. At most one <condition declaration> shall specify a <condition name> that is equivalent to *CN* and has the same scope as *CN*.
- 3) <condition name> is *considered to be defined*, within its scope, for the SQLSTATE value specified by <sqlstate value>.

Access Rules

None.

General Rules

None.

13.4 <SQL variable declaration>

Function

Declare one or more variables.

Format

```
<SQL variable declaration> ::=  
    DECLARE <SQL variable name list>  
        <data type> [ <default clause> ]
```

```
<SQL variable name list> ::=  
    <SQL variable name> [ { <comma> <SQL variable name> }... ]
```

Syntax Rules

- 1) The specified <data type> is the declared type of each variable declared by the <SQL variable declaration>.

Access Rules

None.

General Rules

- 1) When the variable associated with the <SQL variable declaration> is created, its default value *DV* is derived according to the General Rules of Subclause 9.3, “<default clause>”. Let *SV* be the variable defined by the <SQL variable declaration>. The value of *SV* is set to *DV* by the effective invocation of the following SQL-statement:

```
SET SV = DV
```

13.5 <assignment statement>

Function

Assign a value to an SQL variable, SQL parameter, host parameter, or host variable.

Format

```
<assignment statement> ::=
    <singleton variable assignment>
  | <multiple variable assignment>

<multiple variable assignment> ::=
    SET <update target list> <equals operator> <assigned row>

<assignment target list> ::=
    <left paren> <assignment target> [ { <comma> <assignment target> }... ] <right paren>

<singleton variable assignment> ::=
    SET <assignment target> <equals operator> <assignment source>

<assignment target> ::=
    <target specification>
  | <modified field reference>
  | <mutator reference>

<assignment source> ::=
    <value expression>
  | <contextually typed source>

<contextually typed source> ::=
    <implicitly typed value specification>
  | <contextually typed row value expression>

<modified field reference> ::=
    <modified field target> <period> <field name>

<modified field target> ::=
    <target specification>
  | <left paren> <target specification> <right paren>
  | <modified field reference>

<mutator reference> ::=
    <mutated target specification> <period> <method name>

<mutated target specification> ::=
    <target specification>
  | <left paren> <target specification> <right paren>
  | <mutator reference>
```

13.5 <assignment statement>

Syntax Rules

- 1) An <assignment statement> *A* that contains a <multiple variable assignment> is effectively replaced by a <compound statement> *CS* as follows:
 - a) Let *ATL* be the <assignment target list> contained in *A*, let *ATN* be the number of <assignment target>s contained in *ATL*, and let *AR* be the <assigned row> contained in *A*.
 - b) *ATN* shall be equal to the degree of *AR*.
 - c) Let *X* be an arbitrary <SQL variable name> that is not equivalent to any <target specification> contained in *A*.
 - d) Let *XT* be the declared type of *AR*.
 - e) Let *AT_i*, $1 \text{ (one)} \leq i \leq \text{UTN}$, be the *i*-th <assignment target> contained in *ATL* and let *FN_i* be the <field name> of the *i*-th field of *AR*.
 - f) *CS* is:

```

BEGIN
  DECLARE X XT ;
  SET X = AR ;
  SET AT1 = X . FN1 ;
  . . .
  SET ATATN = X . FNATN ;
END

```

- 2) A <column reference> immediately contained in a <modified field target> or a <mutated target specification> shall be a new transition variable column reference.

NOTE 17 – “New transition variable column reference” is defined in Subclause 6.6, “<identifier chain>”, in ISO/IEC 9075-2.

- 3) The declared type of the <target specification> simply contained in a <mutator reference> *MR* shall be a user-defined type.
- 4) If <assignment target> immediately contains a <mutator reference>, then let *TS* be the <mutated target>, let *FN* be the <method name>, and let *AS* be the <assignment source>. The <assignment statement> is equivalent to:

```
SET TS = TS.FN ( AS )
```

NOTE 18 – The preceding rule is applied recursively until the <assignment target> no longer contains a <mutator reference>.

- 5) If <assignment target> is a <modified field reference> *FR*, then:
 - a) Let *F* be the field identified by <field name> simply contained in <assignment target> and not simply contained in <modified field target>.
 - b) Let *AS* be the <assignment source>.
 - c) The Syntax Rules of Subclause 9.2, “Store assignment”, in ISO/IEC 9075-2 are applied to *F* and *AS* as *TARGET* and *VALUE*, respectively.

- 6) If the <assignment target> simply contains an <embedded variable name> or a <host parameter specification>, then <assignment source> shall not simply contain an <embedded variable name> or a <host parameter specification>.
- 7) If the <assignment target> simply contains a <column reference>, an <SQL variable reference>, or an <SQL parameter reference> and the <assignment source> is a <value expression>, then the Syntax Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9075-2 are applied to <assignment target> and <assignment source> as *TARGET* and *VALUE*, respectively.
- 8) If the <assignment target> simply contains an <embedded variable name> or a <host parameter specification> and the <assignment source> is a <value expression>, then the Syntax Rules of Subclause 9.1, "Retrieval assignment", in ISO/IEC 9075-2 are applied to <assignment target> and <assignment source> as *TARGET* and *VALUE*, respectively.
- 9) If <target array element specification> is specified, then:
 - a) <target array reference> contained in an <assignment target> shall not be <column reference>.
 - b) The Syntax Rules of Subclause 9.2, "Store assignment", apply to an arbitrary site whose declared type is the declared type of the <target specification> and the <assignment source> as *TARGET* and *VALUE*, respectively.
- 10) A <contextually typed row value expression> that is specified as a <contextually typed source> shall not contain a <default specification>.

Access Rules

None.

General Rules

- 1) If <assignment target> is a <target specification> that is a <column reference> *T*, an <SQL variable reference> to an SQL variable *T*, or an <SQL parameter reference> to an SQL parameter *T* of an SQL-invoked routine, then the value of <assignment source> is assigned to *T* according to the General Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9075-2, with <assignment source> and *T* as *VALUE* and *TARGET*, respectively.
- 2) If <assignment target> is a <target specification> that is the <embedded variable name> of a host variable *T* or the <host parameter specification> of a host parameter *T*, then the value of <assignment source> is assigned to *T* according to the General Rules of Subclause 9.1, "Retrieval assignment", in ISO/IEC 9075-2, with <assignment source> and *T* as *VALUE* and *TARGET*, respectively.
- 3) If <assignment target> is a <target specification> that is a new transition variable column reference, then let *C* be the column identified by the <column reference> and let *R* be the row that is to be replaced by that transition variable. For each transition variable *TV* that is a replacement for a subrow of *R* or for a superrow of *R* in a table in which *C* is a column, the value of <assignment source> is assigned to *TV.C* according to the General Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9075-2, with <assignment source> and *TV.C* as *VALUE* and *TARGET*, respectively.

13.5 <assignment statement>

- 4) If <assignment target> is a <modified field reference> *FR*, then let *T* be the <target specification> simply contained in *FR*. Let F_i be a field identified by each <field name> simply contained in *FR*. Let *FT* be the field identified by the <field name> that is simply contained in <assignment target> and that is not simply contained in <modified field target>.
 - a) If the value of *T* or of any F_i is the null value, then an exception condition is raised: *data exception — null value in field reference*.
 - b) Otherwise, the value of <assignment source> is assigned to *FT* according to the General Rules of Subclause 9.2, "Store assignment", in ISO/IEC 9075-2, with <assignment source> and *FT* as *VALUE* and *TARGET*, respectively.
- 5) If <target array element specification> is specified, then:

Case:

 - a) If the value of <target specification>, denoted by *C*, is null, then an exception condition is raised: *data exception — null value in array target*.
 - b) Otherwise:
 - i) Let *N* be the maximum cardinality of *C*.
 - ii) Let *M* be the cardinality of the value of *C*.
 - iii) Let *I* be the value of the <simple value specification> immediately contained in <target specification>.
 - iv) Let *EDT* be the element type of *C*.
 - v) Case:
 - 1) If *I* is greater than zero and less than or equal to *M*, then the value of *C* is replaced by an array *A* with element type *EDT* and cardinality *M* derived as follows:
 - A) For *j* varying from 1 (one) to *I*−1 and from *I*+1 to *M*, the *j*-th element in *A* is the value of the *j*-th element in *C*.
 - B) The *I*-th element of *A* is set to the value of the <assignment source>, denoted by *SV*, by applying the General Rules of Subclause 9.2, "Store assignment", to the *I*-th element of *A* and *SV* as *TARGET* and *VALUE*, respectively.
 - 2) If *I* is greater than *M* and less than or equal to *N*, then the value of *C* is replaced by an array *A* with element type *EDT* and cardinality *I* derived as follows:
 - A) For *j* varying from 1 (one) to *M*, the *j*-th element in *A* is the value of the *j*-th element in *C*.
 - B) For *j* varying from *M*+1 to *I*, the *j*-th element in *A* is the null value.
 - C) The *I*-th element of *A* is set to the value of the <assignment source>, denoted by *SV*, by applying the General Rules of Subclause 9.2, "Store assignment", to the *I*-th element of *A* and *SV* as *TARGET* and *VALUE*, respectively.
 - 3) Otherwise, an exception condition is raised: *data exception — array element error*.

Conformance Rules

- 1) Without Feature P006, “Multiple assignment”, no <assignment statement> shall contain a <multiple variable assignment>.

13.6 <case statement>

Function

Provide conditional execution based on truth of <search condition>s or on equality of operands.

Format

```

<case statement> ::=
    <simple case statement>
    | <searched case statement>

<simple case statement> ::=
    CASE <simple case operand 1>
        <simple case statement when clause>...
    [ <case statement else clause> ]
    END CASE

<searched case statement> ::=
    CASE
        <searched case statement when clause>...
    [ <case statement else clause> ]
    END CASE

<simple case statement when clause> ::=
    WHEN <simple case operand 2>
        THEN <SQL statement list>

<searched case statement when clause> ::=
    WHEN <search condition>
        THEN <SQL statement list>

<case statement else clause> ::=
    ELSE <SQL statement list>

<simple case operand 1> ::=
    <row value predicand>
    | <overlaps predicate part 1>

<simple case operand 2> ::=
    <row value predicand>
    | <comparison predicate part 2>
    | <between predicate part 2>
    | <in predicate part 2>
    | <character like predicate part 2>
    | <octet like predicate part 2>
    | <similar predicate part 2>
    | <null predicate part 2>
    | <quantified comparison predicate part 2>
    | <match predicate part 2>
    | <overlaps predicate part 2>
    | <distinct predicate part 2>
    | <member predicate part 2>
    | <submultiset predicate part 2>
    | <set predicate part 2>
    | <type predicate part 2>

```

Syntax Rules

- 1) If a <case statement> specifies a <simple case statement>, then let *SCO1* be the <simple case operand 1>:
 - a) *SCO1* shall not generally contain a <routine invocation> whose subject routines include an SQL-invoked routine that is possibly non-deterministic or that possibly modifies SQL-data.
 - b) If *SCO1* is <overlaps predicate part 1>, then each <simple case operand 2> shall be <overlaps predicate part 2>. If *SCO1* is <row value predicand>, then each <simple case operand 2> shall not be <overlaps predicate part 2>.
 - c) If the <simple case operand 2> of the *i*-th <simple case statement when clause> is a <row value predicand>, then let *SCO2_i* be the <equals operator> concatenated with the <simple case operand 2> of the *i*-th <simple case statement when clause>; otherwise, let *SCO2_i* be the <simple case operand 2> of the *i*-th <simple case statement when clause>.
 - d) Let *SSL_i* be the <SQL statement list> of the *i*-th <simple case statement when clause>.
 - e) If <case statement else clause> is specified, then let *CSEC* be the <case statement else clause>; otherwise, let *CSEC* be a character string of length 0 (zero).
 - f) The <simple case statement> is equivalent to a <searched case statement> in which the *i*-th <searched case statement when clause> takes the form:

WHEN *SCO1* *SCO2_i* THEN *SSL_i*

- g) The <case statement else clause> of the equivalent <searched case statement> takes the form:

CSEC

Access Rules

None.

General Rules

- 1) Case:
 - a) If the <search condition> of some <searched case statement when clause> in a <case statement> is True , then let *SL* be the <SQL statement list> of the first (leftmost) <searched case statement when clause> whose <search condition> is True .
 - b) If the <case statement> simply contains a <case statement else clause>, then let *SL* be the <SQL statement list> of that <case statement else clause>.
 - c) Otherwise, an exception condition is raised: *case not found for case statement*, and the execution of the <case statement> is terminated immediately.
- 2) Let *N* be the number of <SQL procedure statement>s simply contained in *SL* without an intervening <SQL control statement>. For *i* ranging from 1 to *N*:
 - a) Let *S_i* be the *i*-th such <SQL procedure statement>.

13.6 <case statement>

- b) The General Rules of Subclause 13.5, "<SQL procedure statement>", in ISO/IEC 9075-2, are evaluated with S_i as the *executing statement*.
- c) If the execution of S_i terminates with an unhandled exception condition, then the execution of the <case statement> is terminates with that condition.

Conformance Rules

- 1) Without Feature P004, "Extended CASE statement", both <simple case operand 1> and <simple case operand 2> shall be a <row value predicand> that is a <row value constructor predicand> that is a single <common value expression> or <boolean value predicand>.

13.7 <if statement>

Function

Provide conditional execution based on the truth value of a condition.

Format

```
<if statement> ::=
    IF <search condition>
      <if statement then clause>
      [ <if statement elseif clause>... ]
      [ <if statement else clause> ]
    END IF

<if statement then clause> ::=
    THEN <SQL statement list>

<if statement elseif clause> ::=
    ELSEIF <search condition> THEN <SQL statement list>

<if statement else clause> ::=
    ELSE <SQL statement list>
```

Syntax Rules

- 1) If one or more <if statement elseif clause>s are specified, then the <if statement> is equivalent to an <if statement> that does not contain ELSEIF by performing the following transformation recursively:

```
IF <search condition>
  <if statement then clause>
  <if statement elseif clause 1>
  [ <if statement elseif clause>... ]
  [ <if statement else clause> ]
END IF
```

is equivalent to

```
IF <search condition>
  <if statement then clause>
  ELSE
    IF <search condition 1>
      THEN <statement list 1>
      [ <if statement elseif clause>... ]
      [ <if statement else clause> ]
    END IF
  END IF
```

where <search condition 1> is the <search condition> simply contained in <if statement elseif clause 1> and <statement list 1> is the <SQL statement list> simply contained in <if statement elseif clause 1>.

13.7 <if statement>

Access Rules

None.

General Rules

1) Case:

- a) If the <search condition> immediately contained in the <if statement> evaluates to True , then let SL be the <SQL statement list> immediately contained in the <if statement then clause>.
- b) Otherwise, if an <if statement else clause> is specified, then let SL be the <SQL statement list> immediately contained in the <if statement else clause>.

NOTE 19 – “Otherwise” means that the <search condition> immediately contained in the <if statement> evaluates to False or to Unknown .

2) Let N be the number of <SQL procedure statement>s simply contained in SL without an intervening <SQL control statement>. For i ranging from 1 to N :

- a) Let S_i be the i -th such <SQL procedure statement>.
- b) The General Rules of Subclause 13.5, "<SQL procedure statement>", in ISO/IEC 9075-2, are evaluated with S_i as the *executing statement*.
- c) If the execution of S_i terminates with an unhandled exception condition, then the execution of the <if statement> is terminated and the condition remains active.

13.8 <iterate statement>

Function

Terminate the execution of an iteration of an iterated SQL-statement.

Format

```
<iterate statement> ::=  
    ITERATE <statement label>
```

Syntax Rules

- 1) <statement label> shall be the <beginning label> of some iterated SQL-statement *IS* that contains <iterate statement> without an intervening <SQL-schema statement>.
- 2) Let *SSL* be the <SQL statement list> simply contained in *IS*.

Access Rules

None.

General Rules

- 1) The execution of *SSL* is terminated.

NOTE 20 – If the iteration condition for *IS* is True or if *IS* does not have an iteration condition, then the next iteration of *SSL* commences immediately. If the iteration condition for *IS* is False, then there is no next iteration of *SSL*.

13.9 <leave statement>

13.9 <leave statement>

Function

Continue execution by leaving a labeled statement.

Format

```
<leave statement> ::=  
    LEAVE <statement label>
```

Syntax Rules

- 1) <statement label> shall be the <beginning label> of some <SQL procedure statement> *S* that contains <leave statement> *L* without an intervening <SQL-schema statement>.

Access Rules

None.

General Rules

- 1) For every <compound statement> *CS* that is contained in *S* and that contains the <leave statement>:
 - a) For every open cursor *CR* that is declared in the <local cursor declaration list> of *CS*, the following statement is effectively executed:

```
CLOSE CR
```
 - b) The variables, cursors, and handlers specified in the <local declaration list>, the <local cursor declaration list>, and the <local handler declaration list> of *CS* are destroyed.
- 2) The execution of *S* is terminated.

13.10 <loop statement>

Function

Repeat the execution of a statement.

Format

```
<loop statement> ::=  
    [ <beginning label> <colon> ]  
    LOOP  
    <SQL statement list>  
    END LOOP [ <ending label> ]
```

Syntax Rules

- 1) Let *LS* be the <loop statement>.
- 2) If *LS* is contained in another <SQL control statement> and *LS* does not specify a <beginning label>, then an implementation-dependent <beginning label> that is not equivalent to any other <statement label> contained in the outermost containing <SQL control statement> is implicit.
- 3) If <ending label> is specified, then a <beginning label> shall be specified that is equivalent to <ending label>.
- 4) The scope of the <beginning label> is *LS* excluding every <SQL schema statement> contained in *LS*. <beginning label> shall not be equivalent to any other <beginning label> contained in *LS* excluding every <SQL schema statement> contained in *LS*.

Access Rules

None.

General Rules

- 1) Let *SSL* be the <SQL statement list> and let *CCS* be the <compound statement>

```
BEGIN NOT ATOMIC SSL END
```

The General Rules of Subclause 13.5, "<SQL procedure statement>", of ISO/IEC 9075-2, are evaluated repeatedly with *CCS* as the *executing statement*.

NOTE 21 – The occurrence of an exception condition or the execution of a <leave statement> may also cause execution of *LS* to be terminated; see Subclause 6.2.3.7, "Exceptions", in ISO/IEC 9075-1, and Subclause 13.9, "<leave statement>", respectively. Some actions taken by a condition handler might also cause execution of *LS* to be terminated; see Subclause 13.2, "<handler declaration>".

13.11 <while statement>

Function

While a specified condition is True , repeat the execution of a statement.

Format

```
<while statement> ::=
    [ <beginning label> <colon> ]
    WHILE <search condition> DO
        <SQL statement list>
    END WHILE [ <ending label> ]
```

Syntax Rules

- 1) Let *WS* be the <while statement>.
- 2) If *WS* is contained in another <SQL control statement> and *WS* does not specify a <beginning label>, then an implementation-dependent <beginning label> that is not equivalent to any other <statement label> contained in the outermost containing <SQL control statement> is implicit.
- 3) If <ending label> is specified, then a <beginning label> shall be specified that is equivalent to <ending label>.
- 4) The scope of the <beginning label> is *WS* excluding every <SQL schema statement> contained in *WS*. <beginning label> shall not be equivalent to any other <beginning label> contained in *WS* excluding every <SQL schema statement> contained in *WS*.

Access Rules

None.

General Rules

- 1) The <search condition> is evaluated.
- 2) Case:
 - a) If the <search condition> evaluates to False or Unknown , then execution of *WS* is terminated.
 - b) Let *SSL* be the <SQL statement list> and let *CCS* be the <compound statement>

```
BEGIN NOT ATOMIC SSL END
```

If the <search condition> evaluates to True , then the General Rules of Subclause 13.5, "<SQL procedure statement>", of ISO/IEC 9075-2, are evaluated with *CCS* as the *executing statement* and the execution of *WS* is repeated.

NOTE 22 – The occurrence of an exception condition or the execution of a <leave statement> may also cause execution of *WS* to be terminated; see Subclause 6.2.3.7, "Exceptions", in ISO/IEC 9075-1, and Subclause 13.9, "<leave statement>", respectively. Some actions taken by a condition handler might also cause execution of *WS* to be terminated; see Subclause 13.2, "<handler declaration>".

13.12 <repeat statement>

Function

Repeat the execution of a statement.

Format

```
<repeat statement> ::=  
  [ <beginning label> <colon> ]  
  REPEAT  
    <SQL statement list>  
    UNTIL <search condition>  
  END REPEAT [ <ending label> ]
```

Syntax Rules

- 1) Let *RS* be the <repeat statement>.
- 2) If *RS* is contained in another <SQL control statement> and *RS* does not specify a <beginning label>, then an implementation-dependent <beginning label> that is not equivalent to any other <statement label> contained in the outermost containing <SQL control statement> is implicit.
- 3) If <ending label> is specified, then a <beginning label> shall be specified that is equivalent to <ending label>.
- 4) The scope of the <beginning label> is *RS* excluding every <SQL schema statement> contained in *RS*. <beginning label> shall not be equivalent to any other <beginning label> contained in *RS* excluding every <SQL schema statement> contained in *RS*.

Access Rules

None.

General Rules

- 1) Let *SSL* be the <SQL statement list> and let *CCS* be the <compound statement>

```
BEGIN NOT ATOMIC SSL END
```

the General Rules of Subclause 13.5, "<SQL procedure statement>", of ISO/IEC 9075-2, are evaluated with *CCS* as the *executing statement* and then <search condition> is evaluated.

NOTE 23 – The occurrence of an exception condition or the execution of a <leave statement> may also cause execution of *RS* to be terminated; see Subclause 6.2.3.7, "Exceptions", in ISO/IEC 9075-1, and Subclause 13.9, "<leave statement>", respectively. Some actions taken by a condition handler might also cause execution of *RS* to be terminated; see Subclause 13.2, "<handler declaration>".

- 2) If the <search condition> evaluates to *False* or *Unknown*, then the execution of *RS* is repeated; otherwise, execution of *RS* is terminated.

13.13 <for statement>

13.13 <for statement>

Function

Execute a statement for each row of a table.

Format

```
<for statement> ::=
  [ <beginning label> <colon> ]
  FOR <for loop variable name> AS
  [ <cursor name> [ <cursor sensitivity> ] CURSOR FOR ]
  <cursor specification>
  DO <SQL statement list>
  END FOR [ <ending label> ]
```

```
<for loop variable name> ::= <identifier>
```

Syntax Rules

- 1) Let *FCS* be the <cursor specification> of the <for statement> *FS*.
- 2) If *FS* is contained in another <SQL control statement> and *FS* does not specify a <beginning label>, then an implementation-dependent <beginning label> that is not equivalent to any other <statement label> contained in the outermost containing <SQL control statement> is implicit.
- 3) If <ending label> is specified, then a <beginning label> shall be specified that is equivalent to <ending label>.
- 4) If <cursor name> is specified, then let *CN* be that <cursor name>. Otherwise, let *CN* be an implementation-dependent <cursor name> that is not equivalent to any other <cursor name> in the outermost containing <SQL-client module definition> or <SQL-invoked routine>.
- 5) Let *QE* be the <query expression> of *FCS*. Each column of the table specified by *QE* shall have a <column name> that is not equivalent to any other <column name> in the table specified by *QE*. Let *V1*, *V2*, . . . , *Vn* be those <column name>s. Let *DT1*, *DT2*, . . . , *DTn* be the declared types of the respective columns.
- 6) Let *BL*, *FLVN*, and *SLL* be the <beginning label>, <for loop variable name>, and <SQL statement list> of *FS*, respectively.
 - a) Let *AT_END* be an implementation-dependent <SQL variable name> that is not equivalent to any other <SQL variable name> or any <SQL parameter name> contained in the outermost containing <SQL-server module definition>, <SQL-invoked routine>, or <compound statement>.
 - b) Let *NOT_FOUND* be an implementation-dependent <condition name> that is not equivalent to any other <condition name> contained in the outermost containing <SQL-server module definition>, <SQL-invoked routine>, or <compound statement>.
 - c) Let *CS* be the explicit or implicit <cursor sensitivity>.

7) *FS* is equivalent to:

```
BL: BEGIN NOT ATOMIC
    FLVN: BEGIN NOT ATOMIC
        DECLARE CN CS CURSOR FOR FCS
        DECLARE V1 DT1;
        DECLARE V2 DT2;
        .
        .
        .
        DECLARE Vn DTn;
        DECLARE AT_END BOOLEAN DEFAULT FALSE;
        DECLARE NOT_FOUND CONDITION FOR SQLSTATE '02000';
    BEGIN NOT ATOMIC
        DECLARE CONTINUE HANDLER FOR NOT_FOUND
            SET AT_END = TRUE;

        OPEN CN;
        FETCH CN INTO V1, V2, ..., Vn;
        WHILE NOT AT_END DO
            SLL;
            BEGIN NOT ATOMIC
                FETCH CN INTO V1, V2, ..., Vn;
            END;
        END WHILE;
        CLOSE CN;
    END;
END FLVN;
END BL
```

- 8) *SLL* shall not contain, without an intervening <SQL-invoked routine> or <SQL schema statement>, a <leave statement> that specifies *FLVN*.
- 9) *SLL* shall not contain either a <commit statement> or a <rollback statement>.
- 10) *SLL* shall not contain without an intervening <SQL-invoked routine or <SQL schema statement> a <fetch statement>, an <open statement>, or a <close statement> that specifies *CN*.

Access Rules

None.

General Rules

None.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

14 Dynamic SQL

This Clause modifies Clause 19, "Dynamic SQL", in ISO/IEC 9075-2.

14.1 <prepare statement>

This Subclause modifies Subclause 19.6, "<prepare statement>", in ISO/IEC 9075-2.

Function

Prepare a statement for execution.

Format

No additional Format items.

Syntax Rules

No additional Syntax Rules.

Access Rules

No additional Access Rules.

General Rules

- 1) Insert after GR6)a)xxix) If *DP* is the <assignment target> simply contained in an <assignment statement> *AS*, then

Case:

 - a) If the <assignment source> immediately contains a <null specification>, then *DT* is undefined.
 - b) Otherwise, *DT* is the declared type of the <value expression> simply contained in the <assignment source> of *AS*.

- 2) Insert after GR6)a)xxix) If *DP* is the <value expression> simply contained in an <assignment source> in an <assignment statement> *AS* or if *DP* represents the value of a subfield *SF* of the declared type of such a <value expression>, then let *RT* be the declared type of the <assignment target> simply contained in *AS*.

Case:

 - a) If *DP* is the <value expression> simply contained in the <assignment source>, then *DT* is *RT*.
 - b) Otherwise, *DT* is the declared type of the subfield of *RT* that corresponds to *SF*.

14.1 <prepare statement>

- 3) Insert after GR6)a)xxix) If *DP* is a <value expression> simply contained in a <simple case operand 1> or a <simple case operand 2> of a <simple case statement> *CS*, or if *DP* represents the value of a subfield *SF* of such a <value expression>, then let *RT* be the result of applying the Syntax Rules of Subclause 9.3, "Data types of results of aggregations", in ISO/IEC 9075-2 to the <value expression>s simply contained in the <simple case operand 1> and all <simple case operand 2>s simply contained in *CS*.

Case:

- a) If *DP* is a <value expression> simply contained in the <simple case operand 1> or <simple case operand 2> of *CS*, then *DT* is *RT*.
- b) Otherwise, *DT* is the declared type of the subfield of *RT* that corresponds to *SF*.

15 Embedded SQL

This Clause modifies Clause 20, "Embedded SQL", in ISO/IEC 9075-2.

15.1 <embedded SQL host program>

This Subclause modifies Subclause 20.1, "<embedded SQL host program>", in ISO/IEC 9075-2.

Function

Specify an <embedded SQL host program>.

Format

No additional Format items.

Syntax Rules

- 1) Insert this SR An <SQL variable declaration> that is contained in an <embedded SQL host program> shall precede in the text of that <embedded SQL host program> any SQL-statement that references the <SQL variable name> of the <SQL variable declaration>.
- 2) Insert this SR An <SQL variable name> contained in an <SQL variable declaration> that is immediately contained in an <embedded SQL host program> shall not be equivalent to any other <SQL variable name> or <embedded variable name> contained in any other <SQL variable declaration> or <host variable definition>, respectively, that is immediately contained in the <embedded SQL host program>.
- 3) Insert this SR If a <handler declaration> is immediately contained in an <embedded SQL host program> with no intervening <compound statement>, then any <condition value> contained in that <handler declaration> shall not be equivalent to the <condition value> of any other <handler declaration> immediately contained in that <embedded SQL host program>.
- 4) Insert before SR21)k M contains one <SQL variable declaration> for each <SQL variable declaration> contained in H . Each <SQL variable declaration> of M is a copy of the corresponding <SQL variable declaration> of H .
- 5) Insert before SR21)l M contains one <handler declaration> for each <handler declaration> contained in H . Each <handler declaration> of M is a copy of the corresponding <handler declaration> of H .
- 6) Replace SR22)c Each <embedded SQL statement> that contains a <declare cursor>, a <dynamic declare cursor>, an <SQL variable declaration>, an <SQL-invoked routine>, or a <temporary table declaration> has been deleted, and every <embedded SQL statement> that contains an <embedded exception declaration> has been replaced with statements of the host language that will have the effect specified by the General Rules of Subclause 20.2, "<embedded exception declaration>".

SC32 N00745 = WG3:VIE-006 = H2-2002-008
15.1 <embedded SQL host program>

Access Rules

No additional Access Rules.

General Rules

No additional General Rules.

16 Diagnostics management

This Clause modifies Clause 22, "Diagnostics management", in ISO/IEC 9075-2.

16.1 <get diagnostics statement>

This Subclause modifies Subclause 22.1, "<get diagnostics statement>", in ISO/IEC 9075-2.

Function

Get exception or completion condition information from the diagnostics area.

Format

```
<get diagnostics statement> ::=
    GET [ <which area> ] DIAGNOSTICS <SQL diagnostics information>

<which area> ::=
    CURRENT
    | STACKED <condition information item name> ::=
      !! All alternatives from ISO/IEC 9075-2
    | CONDITION_IDENTIFIER
```

Syntax Rules

- 1) If <which area> is not specified, then CURRENT is implicit.
- 2) Table 1, "<identifier>s for use with <get diagnostics statement>", modifies Table 29, "<identifier>s for use with <get diagnostics statement>", in ISO/IEC 9075-2.

Table 1—<identifier>s for use with <get diagnostics statement>

<identifier>	Data Type
<statement information item name>s	
<i>All alternatives from ISO/IEC 9075-2</i>	
<condition information item name>s	
<i>All alternatives from ISO/IEC 9075-2</i>	
CONDITION_IDENTIFIER	character varying (L)

Access Rules

No additional Access Rules.

16.1 <get diagnostics statement>

General Rules

- 1) Table 2, “SQL-statement codes”, modifies Table 30, “SQL-statement codes”, in ISO/IEC 9075-2.

Table 2—SQL-statement codes

SQL-statement	Identifier	Code
<i>All alternatives from ISO/IEC 9075-2</i>		
<assignment statement>	ASSIGNMENT	5
<case statement>	CASE	86
<compound statement>	BEGIN END	12
<drop module statement>	DROP MODULE	28
<for statement>	FOR	46
<if statement>	IF	88
<iterate statement>	ITERATE	102
<leave statement>	LEAVE	89
<loop statement>	LOOP	90
<resignal statement>	RESIGNAL	91
<repeat statement>	REPEAT	95
<signal statement>	SIGNAL	92
<SQL-server module definition>	CREATE MODULE	51
<while statement>	WHILE	97

- 2) Replace GR 1) Case:
- a) If <which area> specifies CURRENT, then let *DA* be the first diagnostics area.
 - b) If <which area> specifies STACKED, then let *DA* be the second diagnostics area.
- 3) Insert after GR 1) If <which area> specifies STACKED and no condition handler is activated, then an exception condition is raised: *diagnostics exception — stacked diagnostics accessed without active handler*.
- 4) Insert before GR4)n) If the value of the RETURNED_SQLSTATE corresponds to *unhandled user-defined exception*, then the value of CONDITION_IDENTIFIER is the <condition name> of the user-defined exception.
- 5) Insert before GR4)p) If COMMAND_FUNCTION or DYNAMIC_FUNCTION identifies a <signal statement> or <resignal statement>, then the values of CLASS_ORIGIN, SUBCLASS_ORIGIN, CONSTRAINT_CATALOG, CONSTRAINT_SCHEMA, CONSTRAINT_NAME, CATALOG_NAME, SCHEMA_NAME, TABLE_NAME, COLUMN_NAME, CURSOR_NAME, MESSAGE_TEXT, MESSAGE_LENGTH, and MESSAGE_OCTET_LENGTH are not set as specified in ISO/IEC 9075-2, but instead are set as specified in Subclause 16.2, “<signal statement>”, and Subclause 16.3, “<resignal statement>”, in this part of ISO/IEC 9075.

Conformance Rules

- 1) Without Feature P007, “Enhanced diagnostics management”, no <get diagnostics statement> shall contain a <which area>.

16.2 <signal statement>

16.2 <signal statement>**Function**

Signal an exception condition.

Format

```

<signal statement> ::=
    SIGNAL <signal value>
        [ <set signal information> ]

<signal value> ::=
    <condition name>
    | <sqlstate value>

<set signal information> ::=
    SET <signal information item list>

<signal information item list> ::=
    <signal information item> [ { <comma> <signal information item> }... ]

<signal information item> ::=
    <condition information item name> <equals operator> <simple value specification>

```

Syntax Rules

- 1) Case:
 - a) If <signal value> immediately contains <condition name>, then:
 - i) Let *CN* be the <condition name> contained in the <signal statement>.
 - ii) The <signal statement> shall be contained in the scope of a <condition name> equivalent to *CN*. Let *CNS* be the innermost such scope.
 - b) Otherwise, let *C* be the SQLSTATE value defined by <sqlstate value> and let *CN* be a zero-length string.
- 2) <condition information item name> shall specify CLASS_ORIGIN, SUBCLASS_ORIGIN, CONSTRAINT_CATALOG, CONSTRAINT_SCHEMA, CONSTRAINT_NAME, CATALOG_NAME, SCHEMA_NAME, TABLE_NAME, COLUMN_NAME, CURSOR_NAME, or MESSAGE_TEXT. No alternative for <condition information item name> shall be specified more than once in <set signal information>.
- 3) The data type of a <condition information item name> contained in <signal information item> shall be the data type specified in Table 1, “<identifier>s for use with <get diagnostics statement>”.

Access Rules

None.

General Rules

- 1) Let *N* be the value of the statement information item NUMBER in the first diagnostics area before the execution of the <signal statement>. The first diagnostics area is emptied. The value of the statement information item NUMBER in the diagnostics area is set to 1 (one) and the statement information item MORE is set to 'N'.

The statement information item COMMAND_FUNCTION is set to 'SIGNAL' and the statement information item DYNAMIC_FUNCTION field is set to a zero-length string.

- 2) Let *CA* be the first condition area in the first diagnostics area. The condition information item CONDITION_IDENTIFIER in *CA* is set to *CN*.

Case:

- a) If *CN* is considered to be defined for an SQLSTATE value, then the condition information item RETURNED_SQLSTATE in *CA* is set to the value for which *CN* is considered to be defined within *CNS*.

NOTE 24 – “considered to be defined for” is defined in Subclause 13.3, “<condition declaration>”.

- b) If <sqlstate value> is specified, then the condition information item RETURNED_SQLSTATE in *CA* is set to <sqlstate value>.
- c) Otherwise, the condition information item RETURNED_SQLSTATE in *CA* is set to a zero-length string.

- 3) The condition information items CLASS_ORIGIN, SUBCLASS_ORIGIN, CONSTRAINT_CATALOG, CONSTRAINT_SCHEMA, CONSTRAINT_NAME, CATALOG_NAME, SCHEMA_NAME, TABLE_NAME, COLUMN_NAME, CURSOR_NAME, and MESSAGE_TEXT in *CA* are set to a zero-length string. The condition information items MESSAGE_LENGTH and MESSAGE_OCTET_LENGTH in *CA* are set to 0 (zero).

- 4) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with “PUSH” as *OPERATION* and the diagnostics area stack as *STACK*.

- 5) Condition handling mode becomes in effect in the SQL-session.

- 6) If <set signal information> is specified, then let *SSI* be the <set signal information>. Otherwise, let *SSI* be a zero-length string. The following <resignal statement> is effectively executed without further Syntax Rule checking:

```
RESIGNAL SSI
```

16.3 <resignal statement>

Function

Resignal an exception condition.

Format

```
<resignal statement> ::=  
    RESIGNAL  
    [ <signal value> ]  
    [ <set signal information> ]
```

Syntax Rules

- 1) Let *RS* be the <resignal statement>.
- 2) If <signal value> is specified, then
Case:
 - a) If <signal value> immediately contains <condition name>, then:
 - i) Let *CN* be the <condition name> contained in *RS*.
 - ii) The <resignal statement> shall be contained within the scope a <condition name> equivalent to *CN*. Let *CNS* be the innermost such scope.
 - b) Otherwise, let *C* be the SQLSTATE value defined by <sqlstate value> and let *CN* be a zero-length string.

Access Rules

None.

General Rules

- 1) If condition handling mode is not in effect, then an exception condition is raised: *resignal when handler not active*.
- 2) The General Rules of Subclause 22.2, "Pushing and popping the diagnostics area stack", in ISO/IEC 9075-2, are applied with "POP" as *OPERATION* and the diagnostics area stack as *STACK*.
- 3) Let *DA* be the first diagnostics area, let *SA* be the statement area in *DA*, and let *CA* be the first condition area in *DA*.
- 4) If <set signal information> is specified, then for each <signal information item> in <set signal information>:
 - a) The condition information item in *CA* identified by the <signal information name> is set to the value of the <simple value specification>.

- b) If the <signal information name> specifies MESSAGE_TEXT, then the condition information items MESSAGE_LENGTH and MESSAGE_OCTET_LENGTH in CA are set to contain the length in characters and the length in octets of the value of the <simple value specification>, respectively.
- 5) If <signal value> is specified, then the statement information item NUMBER in SA is incremented. If the maximum number of condition areas for diagnostics areas is exceeded, then the value of the statement information field MORE in SA is 'Y' and the last condition area in DA is made vacant. All occupied condition areas in DA are stacked such that the *i*-th condition area is placed at the position of the *i*+1-st condition area in DA.

The statement information items COMMAND_FUNCTION, DYNAMIC_FUNCTION, and CONDITION_IDENTIFIER are set to 'RESIGNAL', a zero-length string, and CN, respectively.

Case:

- a) If CN is considered to be defined for an SQLSTATE value, then the condition information item RETURNED_SQLSTATE in CA is set to the SQLSTATE value for which CN is considered to be defined within CNS.
NOTE 25 – “considered to be defined” is defined in Subclause 13.3, “<condition declaration>”.
 - b) If <sqlstate value> is specified, then the condition information item RETURNED_SQLSTATE in CA is set to <sqlstate value>.
 - c) Otherwise, the condition information item field RETURNED_SQLSTATE in CA is set to a zero-length string.
- 6) Case:
- a) If the condition information item RETURNED_SQLSTATE in CA is not the empty string, then:
 - i) Let *S* be that value.
 - ii) If a handler *H* is the most appropriate handler for *S*, then *H* is activated.
 - iii) If no handler is activated and *S* identifies an SQLSTATE value associated with an exception condition, then this is an *unhandled exception condition* and the <SQL procedure statement> that resulted in execution of *RS* is terminated with this exception condition.

NOTE 26 – If *S* identifies an SQLSTATE value associated with a completion condition, then this is an *unhandled completion condition* and processing continues without altering the flow of control.,
 - b) Otherwise:
 - i) Let *E* be the value of the CONDITION_IDENTIFIER item in CA.
 - ii) If a handler *H* is the most appropriate handler for *E*, then *H* is activated.
 - iii) If there is no appropriate handler for *E*, then this is an *unhandled exception condition* and the <SQL procedure statement> that resulted in execution of *RS* is terminated with the exception condition *unhandled user-defined exception*.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

17 Information Schema

This Clause modifies Clause 5, "Information Schema", in ISO/IEC 9075-11.

17.1 MODULE_COLUMN_USAGE view

Function

Identify the columns owned by a given user on which SQL-server modules defined in this catalog are dependent.

Definition

```
CREATE VIEW MODULE_COLUMN_USAGE AS
  SELECT ROUTINE_CATALOG, ROUTINE_SCHEMA, ROUTINE_NAME,
         TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME, COLUMN_NAME
  FROM DEFINITION_SCHEMA.MODULE_COLUMN_USAGE
  JOIN
    DEFINITION_SCHEMA.SCHEMATA S
  ON ( ( TABLE_CATALOG, TABLE_SCHEMA ) =
      ( S.CATALOG_NAME, S.SCHEMA_NAME ) )
  WHERE ( SCHEMA_OWNER = CURRENT_USER
        OR
          SCHEMA_OWNER IN
            ( SELECT ROLE_NAME
              FROM ENABLED_ROLES ) )
  AND
    MODULE_CATALOG =
      ( SELECT CATALOG_NAME
        FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE MODULE_COLUMN_USAGE
  TO PUBLIC WITH GRANT OPTION;
```

SC32 N00745 = WG3:VIE-006 = H2-2002-008
17.2 MODULE_PRIVILEGES view

17.2 MODULE_PRIVILEGES view

Function

Identify the privileges on SQL-server modules defined in this catalog that are available to or granted by a given user.

Definition

```
CREATE VIEW MODULE_PRIVILEGES AS
  SELECT
    GRANTOR, GRANTEE, MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
    PRIVILEGE_TYPE, IS_GRANTABLE
  FROM DEFINITION_SCHEMA.MODULE_PRIVILEGES
  WHERE ( GRANTEE IN
    ( 'PUBLIC', CURRENT_USER )
    OR
    GRANTEE = CURRENT_USER )
  AND
    MODULE_CATALOG =
    ( SELECT CATALOG_NAME
      FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE MODULE_PRIVILEGES
  TO PUBLIC WITH GRANT OPTION;
```

17.3 MODULE_TABLE_USAGE view

Function

Identify the tables owned by a given user on which SQL-server modules defined in this catalog are dependent.

Definition

```
CREATE VIEW MODULE_TABLE_USAGE AS
  SELECT MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
         TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME
  FROM DEFINITION_SCHEMA.MODULE_TABLE_USAGE
  JOIN
    DEFINITION_SCHEMA.SCHEMATA S
  ON ( ( TABLE_CATALOG, TABLE_SCHEMA ) =
      ( S.CATALOG_NAME, S.SCHEMA_NAME ) )
  WHERE ( SCHEMA_OWNER = CURRENT_USER
        OR
          SCHEMA_OWNER IN
            ( SELECT ROLE_NAME
              FROM ENABLED_ROLES ) )
  AND
    MODULE_CATALOG =
      ( SELECT CATALOG_NAME
        FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE MODULE_TABLE_USAGE
  TO PUBLIC WITH GRANT OPTION;
```

SC32 N00745 = WG3:VIE-006 = H2-2002-008
17.4 MODULES view

17.4 MODULES view

Function

Identify the SQL-server modules in this catalog that are accessible to a given user.

Definition

```
CREATE VIEW MODULES AS
  SELECT MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
         DEFAULT_CHARACTER_SET_CATALOG, DEFAULT_CHARACTER_SET_SCHEMA,
         DEFAULT_CHARACTER_SET_NAME,
         DEFAULT_SCHEMA_CATALOG, DEFAULT_SCHEMA_NAME,
         CASE
           WHEN EXISTS (
             SELECT *
             FROM DEFINITION_SCHEMA.SCHEMATA AS S
             WHERE ( MODULE_CATALOG, MODULE_SCHEMA ) =
                   ( S.CATALOG_NAME, S.SCHEMA_NAME )
             AND
                   ( SCHEMA_OWNER IN
                     ( 'PUBLIC', CURRENT_USER )
                   OR
                     SCHEMA_OWNER IN
                     ( SELECT ROLE_NAME
                       FROM ENABLED_ROLES ) ) )
             THEN MODULE_DEFINITION
           ELSE NULL
         END AS MODULE_DEFINITION,
         MODULE_AUTHORIZATION, SQL_PATH, MODULE_CREATED, MODULE_LAST_ALTERED
  FROM DEFINITION_SCHEMA.MODULES
 WHERE ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME ) IN
        ( SELECT MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME
          FROM DEFINITION_SCHEMA.MODULE_PRIVILEGES
          WHERE ( SCHEMA_OWNER IN
                 ( 'PUBLIC', CURRENT_USER )
               OR
                 SCHEMA_OWNER IN
                 ( SELECT ROLE_NAME
                   FROM ENABLED_ROLES ) ) )
        AND
        MODULE_CATALOG =
        ( SELECT CATALOG_NAME
          FROM INFORMATION_SCHEMA.CATALOG_NAME );

GRANT SELECT ON TABLE MODULES
  TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) Without Feature T011, "Timestamp in Information Schema", conforming SQL language shall not reference INFORMATION_SCHEMA.MODULES.MODULE_CREATED or INFORMATION_SCHEMA.MODULES.MODULE_LAST_ALTERED.

17.5 ROLE_MODULE_GRANTS view

Function

Identify the privileges on SQL-server modules defined in this catalog that are available to or granted by the currently enabled roles.

Definition

```
CREATE VIEW ROLE_MODULE_GRANTS AS
  SELECT GRANTOR, GRANTEE, MODULE_CATALOG,
         MODULE_SCHEMA, MODULE_NAME, PRIVILEGE_TYPE,
         IS_GRANTABLE
  FROM DEFINITION_SCHEMA.MODULE_PRIVILEGES
 WHERE ( GRANTEE IN
        ( SELECT ROLE_NAME
          FROM ENABLED_ROLES )
        OR
        GRANTOR IN
        ( SELECT ROLE_NAME
          FROM ENABLED_ROLES ) )
 AND
  MODULE_CATALOG =
  ( SELECT CATALOG_NAME
    FROM INFORMATION_SCHEMA.CATALOG_NAME );
```

```
GRANT SELECT ON TABLE ROLE_MODULE_GRANTS
  TO PUBLIC WITH GRANT OPTION;
```

Conformance Rules

- 1) Without Feature T322, "Extended Roles", conforming SQL language shall not reference INFORMATION_SCHEMA.ROLE_MODULE_GRANTS.

17.6 Short name views

This Subclause modifies Subclause 5.79, "Short name views", in ISO/IEC 9075-2.

Function

Provide alternative views that use only identifiers that do not require Feature F391, "Long identifiers".

Definition

```
CREATE VIEW MODULE_COL_USAGE
  ( ROUTINE_CATALOG,    ROUTINE_SCHEMA,    ROUTINE_NAME,
    TABLE_CATALOG,    TABLE_SCHEMA,    TABLE_NAME,
    COLUMN_NAME ) AS
  SELECT ROUTINE_CATALOG, ROUTINE_SCHEMA, ROUTINE_NAME,
         TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME,
         COLUMN_NAME
  FROM INFORMATION_SCHEMA.MODULE_COLUMN_USAGE;

GRANT SELECT ON TABLE MODULE_COL_USAGE
  TO PUBLIC WITH GRANT OPTION;

CREATE VIEW MODULES_S
  ( MODULE_CATALOG,    MODULE_SCHEMA,    MODULE_NAME,
    DEF_CHAR_SET_CAT,  DEF_CHAR_SET_SCH,  DEF_CHAR_SET_NAME,
    DEF_SCHEMA_CATALOG,  DEFAULT_SCHEMA,    MODULE_DEFINITION,
    MODULE_AUTH,        SQL_PATH,          CREATED,
    ALTERED ) AS
  SELECT MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
         DEFAULT_CHARACTER_SET_CATALOG, DEFAULT_CHARACTER_SET_SCHEMA,
         DEFAULT_CHARACTER_SET_NAME,
         DEFAULT_SCHEMA_CATALOG, DEFAULT_SCHEMA, MODULE_DEFINITION,
         MODULE_AUTHORIZATION, SQL_PATH, CREATED,
         LAST_ALTERED
  FROM INFORMATION_SCHEMA.MODULES;

GRANT SELECT ON TABLE MODULES_S
  TO PUBLIC WITH GRANT OPTION;
```

18 Definition Schema

This Clause modifies Clause 6, "Definition Schema", in ISO/IEC 9075-11.

18.1 MODULE_COLUMN_USAGE base table

Function

The MODULE_COLUMN_USAGE table has one row for each column of a table that is explicitly or implicitly identified in the <query expression> of the view being described.

Definition

```
CREATE TABLE MODULE_COLUMN_USAGE (
  MODULE_CATALOG      INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_SCHEMA       INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_NAME         INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_CATALOG      INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_SCHEMA       INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_NAME         INFORMATION_SCHEMA.SQL_IDENTIFIER,
  COLUMN_NAME         INFORMATION_SCHEMA.SQL_IDENTIFIER,

  CONSTRAINT MODULE_COLUMN_USAGE_PRIMARY_KEY
    PRIMARY KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
                 TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME, COLUMN_NAME ),

  CONSTRAINT MODULE_COLUMN_USAGE_CHECK_REFERENCES_COLUMNS
    CHECK ( TABLE_CATALOG <>
           ANY ( SELECT CATALOG_NAME
                 FROM SCHEMATA )
          OR
           ( TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME, COLUMN_NAME ) IN
           ( SELECT TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME, COLUMN_NAME
             FROM COLUMNS ) ),

  CONSTRAINT MODULE_COLUMN_USAGE_FOREIGN_KEY_MODULES
    FOREIGN KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME )
    REFERENCES MODULES,

  CONSTRAINT MODULE_COLUMN_USAGE_CHECK_MODULE_TABLE_USAGE
    CHECK ( MODULE_CATALOG <>
           ANY ( SELECT MODULE_CATALOG
                 FROM SCHEMATA )
          OR
           ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
             TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME ) IN
           ( SELECT MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
             TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME
             FROM MODULE_TABLE_USAGE ) )
)
```

SC32 N00745 = WG3:VIE-006 = H2-2002-008
18.1 MODULE_COLUMN_USAGE base table

Description

- 1) The values of `MODULE_CATALOG`, `MODULE_SCHEMA`, and `MODULE_NAME` are the catalog name, unqualified schema name, and qualified identifier, respectively, of the SQL-server module being described.
- 2) The values of `TABLE_CATALOG`, `TABLE_SCHEMA`, `TABLE_NAME`, and `COLUMN_NAME` are the catalog name, unqualified schema name, qualified identifier, and identifier respectively, of a column that is referenced in the SQL-server module being described.

18.2 MODULE_PRIVILEGES base table

Function

The MODULE_PRIVILEGES table has one row for each execute privilege descriptor on an SQL-server module. It effectively contains a representation of the execute privilege descriptors.

Definition

```
CREATE TABLE MODULE_PRIVILEGES (
  GRANTOR          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  GRANTEE          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_CATALOG  INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_SCHEMA   INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_NAME     INFORMATION_SCHEMA.SQL_IDENTIFIER,
  PRIVILEGE_TYPE  INFORMATION_SCHEMA.CHARACTER_DATA
  CONSTRAINT MODULE_PRIVILEGES_TYPE_CHECK
  CHECK ( PRIVILEGE_TYPE = 'EXECUTE' ),
  IS_GRANTABLE    INFORMATION_SCHEMA.CHARACTER_DATA
  CONSTRAINT MODULE_PRIVILEGES_GRANTABLE_NOT_NULL
  NOT NULL
  CONSTRAINT MODULE_PRIVILEGES_GRANTABLE_CHECK
  CHECK ( IS_GRANTABLE
  IN ( 'YES', 'NO' ) ),

  CONSTRAINT MODULE_PRIVILEGES_PRIMARY_KEY
  PRIMARY KEY ( GRANTOR, GRANTEE, MODULE_CATALOG, MODULE_SCHEMA,
  MODULE_NAME ),

  CONSTRAINT MODULE_PRIVILEGES_FOREIGN_KEY_TABLES
  FOREIGN KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME )
  REFERENCES MODULES,

  CONSTRAINT MODULE_PRIVILEGE_GRANTOR_CHECK
  CHECK ( GRANTOR IN
  ( SELECT ROLE_NAME
  FROM ROLES )
  OR
  GRANTOR IN
  ( SELECT USER_NAME
  FROM USERS ) ),

  CONSTRAINT MODULE_PRIVILEGE_GRANTEE_CHECK
  CHECK ( GRANTEE IN
  ( SELECT ROLE_NAME
  FROM ROLES )
  OR
  GRANTEE IN
  ( SELECT USER_NAME
  FROM USERS ) )
)
```

Description

- 1) The value of GRANTOR is the <authorization identifier> of the user or role who granted execute privileges, on the SQL-server module identified by MODULE_CATALOG, MODULE_SCHEMA, and MODULE_NAME, to the user or role identified by the value of GRANTEE for the privilege being described.
- 2) The value of GRANTEE is the <authorization identifier> of some user or role, or "PUBLIC" to indicate all users, to whom the privilege being described is granted.

18.2 MODULE_PRIVILEGES base table

3) The values of `MODULE_CATALOG`, `MODULE_SCHEMA`, and `MODULE_NAME` are the catalog name, unqualified schema name, and qualified identifier, respectively, of the SQL-server module on which the privilege being described has been granted.

4) The values of `PRIVILEGE_TYPE` have the following meanings:

<code>EXECUTE</code>	The user has <code>EXECUTE</code> privilege on the SQL-server module identified by <code>MODULE_CATALOG</code> , <code>MODULE_SCHEMA</code> , and <code>MODULE_NAME</code> .
----------------------	--

5) The values of `IS_GRANTABLE` have the following meanings:

<code>YES</code>	The privilege being described was granted <code>WITH GRANT OPTION</code> and is thus grantable.
------------------	---

<code>NO</code>	The privilege being described was not granted <code>WITH GRANT OPTION</code> and is thus not grantable.
-----------------	---

18.3 MODULE_TABLE_USAGE base table

Function

The MODULE_TABLE_USAGE table has one row for each table identified by a <table name> simply contained in a <table reference> that is contained in the <query expression> of a view.

Definition

```
CREATE TABLE MODULE_TABLE_USAGE (
  MODULE_CATALOG      INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_SCHEMA       INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_NAME         INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_CATALOG      INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_SCHEMA       INFORMATION_SCHEMA.SQL_IDENTIFIER,
  TABLE_NAME         INFORMATION_SCHEMA.SQL_IDENTIFIER,

  CONSTRAINT MODULE_TABLE_USAGE_PRIMARY_KEY
    PRIMARY KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME,
                 TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME ),

  CONSTRAINT MODULE_TABLE_USAGE_CHECK_REFERENCES_TABLES
    CHECK ( TABLE_CATALOG <>
           ANY ( SELECT CATALOG_NAME
                 FROM SCHEMATA )
          OR
           ( TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME ) IN
           ( SELECT TABLE_CATALOG, TABLE_SCHEMA, TABLE_NAME
             FROM TABLES ) ),

  CONSTRAINT MODULE_TABLE_USAGE_FOREIGN_KEY_MODULES
    FOREIGN KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME )
      REFERENCES MODULES
)
)
```

Description

- 1) The values of MODULE_CATALOG, MODULE_SCHEMA, and MODULE_NAME are the catalog name, unqualified schema name, and qualified identifier, respectively, of the SQL-server module being described.
- 2) The values of TABLE_CATALOG, TABLE_SCHEMA, and TABLE_NAME are the catalog name, unqualified schema name, and qualified identifier, respectively, of a table that is referenced in the SQL-server module being described.

18.4 MODULES base table

Function

The MODULES base table has one row for each SQL-server module.

Definition

```
CREATE TABLE MODULES (
  MODULE_CATALOG          INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_SCHEMA           INFORMATION_SCHEMA.SQL_IDENTIFIER,
  MODULE_NAME             INFORMATION_SCHEMA.SQL_IDENTIFIER,
  DEFAULT_CHARACTER_SET_CATALOG INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT MODULES_DEFAULT_CHARACTER_SET_CATALOG_NOT_NULL
  NOT NULL,
  DEFAULT_CHARACTER_SET_SCHEMA INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT MODULES_DEFAULT_CHARACTER_SET_SCHEMA_NOT_NULL
  NOT NULL,
  DEFAULT_CHARACTER_SET_NAME INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT MODULES_DEFAULT_CHARACTER_SET_NAME_NOT_NULL
  NOT NULL,
  DEFAULT_SCHEMA_CATALOG  INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT MODULES_DEFAULT_SCHEMA_CATALOG_NOT_NULL
  NOT NULL,
  DEFAULT_SCHEMA_NAME     INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT MODULES_DEFAULT_SCHEMA_NAME_NOT_NULL
  NOT NULL,
  MODULE_DEFINITION       INFORMATION_SCHEMA.CHARACTER_DATA,
  MODULE_AUTHORIZATION    INFORMATION_SCHEMA.SQL_IDENTIFIER
  CONSTRAINT AUTHORIZATION_FOREIGN_KEY_USERS REFERENCES USERS,
  SQL_PATH                INFORMATION_SCHEMA.CHARACTER_DATA,
  CREATED                 INFORMATION_SCHEMA.TIME_STAMP,
  LAST_ALTERED           INFORMATION_SCHEMA.TIME_STAMP,

  CONSTRAINT MODULES_PRIMARY_KEY
  PRIMARY KEY ( MODULE_CATALOG, MODULE_SCHEMA, MODULE_NAME ),

  CONSTRAINT MODULES_FOREIGN_KEY_SCHEMATA
  FOREIGN KEY ( MODULE_CATALOG, MODULE_SCHEMA )
  REFERENCES SCHEMATA,

  CONSTRAINT MODULES_FOREIGN_KEY_CHARACTER_SETS
  FOREIGN KEY ( DEFAULT_CHARACTER_SET_CATALOG, DEFAULT_CHARACTER_SET_SCHEMA,
               DEFAULT_CHARACTER_SET_NAME )
  REFERENCES CHARACTER_SETS,

  CONSTRAINT MODULES_FOREIGN_KEY_DEFAULT_SCHEMA_SCHEMATA
  FOREIGN KEY ( DEFAULT_SCHEMA_CATALOG, DEFAULT_SCHEMA_NAME )
  REFERENCES SCHEMATA
)
)
```

Description

- 1) The values of MODULE_CATALOG, MODULE_SCHEMA, and MODULE_NAME are the catalog name, unqualified schema name, and qualified identifier, respectively, of the module name of the SQL-server module being described.
- 2) The values of DEFAULT_CHARACTER_SET_CATALOG, DEFAULT_CHARACTER_SET_SCHEMA, and DEFAULT_CHARACTER_SET_NAME are the catalog name, unqualified schema name, and qualified identifier, respectively, of the character set identified by the implicit or explicit <SQL-server module character set specification>.

- 3) The values of DEFAULT_SCHEMA_CATALOG, and DEFAULT_SCHEMA_NAME are the catalog name, and unqualified schema name, respectively, of the schema identified by the implicit or explicit <SQL-server module schema clause>.
- 4) Case:
 - a) If the character representation of the <SQL-server module definition> that defined the SQL-server module being described can be represented without truncation, then the value of MODULE_DEFINITION is that character representation.
 - b) Otherwise, the value of MODULE_DEFINITION is the null value.

NOTE 27 – Any implicit <column reference>s that were contained in the <SQL-server module definition> are replaced by explicit <column reference>s in MODULE_DEFINITION.
- 5) Case:
 - a) If AUTHORIZATION was specified in <module authorization clause> in the SQL-server module being described, then the value of MODULE_AUTHORIZATION is <module authorization identifier>.
 - b) Otherwise, the value of MODULE_AUTHORIZATION is the null value.
- 6) Case:
 - a) If <SQL-server module path specification> was specified in the <SQL-server module definition> that defined the SQL-server module described by this row and the character representation of the <SQL-server module path specification> can be represented without truncation, then the value of SQL_PATH is that character representation.
 - b) Otherwise, the value of SQL_PATH is the null value.
- 7) The value of CREATED is the value of CURRENT_TIMESTAMP at the time when the SQL-server module being described was created.
- 8) The value of LAST_ALTERED is the value of CURRENT_TIMESTAMP at the time that the SQL-server module being described was last altered. This value is identical to the value of CREATED for SQL-server modules that have never been altered.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

19 Status codes

This Clause modifies Clause 23, "Status codes", in ISO/IEC 9075-2.

19.1 SQLSTATE

This Subclause modifies Subclause 23.1, "SQLSTATE", in ISO/IEC 9075-2.

Table 3, "SQLSTATE class and subclass values", modifies Table 31, "SQLSTATE class and subclass values", in ISO/IEC 9075-2.

Table 3—SQLSTATE class and subclass values

Category	Condition	Class	Subcondition	Subclass
	<i>All alternatives from ISO/IEC 9075-2</i>			
X	case not found for case statement	20	(no subclass)	000
X	data exception	22	(no subclass)	000
			null value in field reference	02A
X	diagnostics exception	0Z	(no subclass)	000
			stacked diagnostics accessed without active handler	002
X	resignal when handler not active	0K	(no subclass)	000
W	warning	01	(no subclass)	000
X	unhandled user-defined exception	45	(no subclass)	000

SC32 N00745 = WG3:VIE-006 = H2-2002-008

20 Conformance

- 1 paragraph deleted.

20.1 Claims of conformance

This Subclause modifies Subclause 8.1.5, "Claims of conformance", in ISO/IEC 9075-1.

Insert this paragraph In addition to the requirements of ISO/IEC 9075-1, Subclause 8.1.5, "Claims of conformance", a claim of conformance to this part of ISO/IEC 9075 shall state whether or not Feature P001, "Stored modules", is supported.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

Annex A (informative)

SQL Conformance Summary

This Annex modifies Appendix A, "SQL Conformance Summary", in ISO/IEC 9075-2.

Replicated paragraph The contents of this Annex summarizes all Conformance Rules, ordered by Feature ID and by Subclause.

- 1) Specifications for Feature P001, "Stored modules":
 - a) Subclause 11.2, "<SQL procedure statement>":
 - i) Without Feature P001, "Stored modules", an <SQL procedure statement> shall not be an <SQL server module definition> or a <drop module statement>.
- 2) Specifications for Feature P004, "Extended CASE statement":
 - a) Subclause 13.6, "<case statement>":
 - i) Without Feature P004, "Extended CASE statement", both <simple case operand 1> and <simple case operand 2> shall be a <row value expression> that is a <row value constructor> that is a single <row value constructor element>.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

Annex B (informative)

Implementation-defined elements

This Annex modifies Appendix B, "Implementation-defined elements", in ISO/IEC 9075-2.

Insert this paragraph This Annex references those features that are identified in the body of this part of ISO/IEC 9075 as implementation-defined.

Insert this paragraph The term *implementation-defined* is used to identify characteristics that may differ between implementations, but that shall be defined for each particular implementation.

- 1) Subclause 4.7, "Diagnostics area":
 - a) An SQL-implementation places information about a completion or exception condition that causes a handler to be activated into the diagnostics area prior to activating the handler. If other conditions are raised, then it is implementation-defined whether the implementation places information about them into the diagnostics area.
- 2) Subclause 8.2, "<sqlstate value>":
 - a) The implicit or explicit character set of the <character string literal> contained in <sqlstate value> shall be the implementation-defined character set in which SQLSTATE parameter values are returned.
 - b) The value of the <character string literal> contained in <sqlstate value> may be composed of a standard SQLSTATE Class value for which an implementation-defined Subclass value is permitted and three characters with the form of an implementation-defined Subclass value.
 - c) The value of the <character string literal> contained in <sqlstate value> may be composed of five characters of which the first two have the form of an implementation-defined Class value.
- 3) Subclause 9.18, "<SQL-server module definition>":
 - a) If <SQL-server module path specification> is not specified, then an <SQL-server module path specification> containing an implementation-defined <schema name list> that includes the explicit or implicit <schema name> of the <SQL-server module name> is implicit.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

Annex C (informative)

Implementation-dependent elements

This Annex modifies Appendix C, "Implementation-dependent elements", in ISO/IEC 9075-2.

Insert this paragraph This Annex references those places where this part of ISO/IEC 9075 states explicitly that the actions of a conforming implementation are implementation-dependent.

Insert this paragraph The term *implementation-dependent* is used to identify characteristics that may differ between implementations, but that are not necessarily specified for any particular implementation.

- 1) Subclause 4.4, "Tables":
 - a) The effective <schema name> of the <schema qualified name> of the declared local temporary table may be thought of as the implementation-dependent SQL-session identifier associated with the SQL-session and the name of the <SQL-server module definition> that contains the <temporary table declaration>.
- 2) Subclause 9.18, "<SQL-server module definition>":
 - a) If the SQL-server module is actually represented in a character set other than the character set identified by the explicit or implicit <SQL-server module character set specification>, then the effects are implementation-dependent.
- 3) Subclause 12.4, "<select statement: single row>":
 - a) The order of assignment of values to targets in the <select target list> is implementation-dependent.
- 4) Subclause 12.7, "<temporary table declaration>":
 - a) If a <temporary table declaration> is contained in an <SQL-client module definition> without an intervening <SQL-server module definition>, then the implementation-dependent <schema name> is effectively derived from the implementation-dependent SQL-session identifier associated with the SQL-session and an implementation-dependent name associated with the SQL-client module that contains the <temporary table declaration>. Otherwise, the implementation-dependent <schema name> is effectively derived from the implementation-dependent SQL-session identifier associated with the SQL-session and the name associated of the <SQL-server module definition> that contains the <temporary table declaration>.

- 5) Subclause 13.1, “<compound statement>”:
 - a) The implicit <beginning label> of a <compound statement> with no explicit <beginning label> is implementation-dependent.
 - b) The variables, cursors, and handlers specified in the <local declaration list>, the <local cursor declaration list>, and the <local handler declaration list> of a <compound statement> are created in an implementation-dependent order.
- 6) Subclause 13.10, “<loop statement>”:
 - a) The implicit <beginning label> of a <loop statement> with no explicit <beginning label> is implementation-dependent.
- 7) Subclause 13.11, “<while statement>”:
 - a) The implicit <beginning label> of a <while statement> with no explicit <beginning label> is implementation-dependent.
- 8) Subclause 13.12, “<repeat statement>”:
 - a) The implicit <beginning label> of a <repeat statement> with no explicit <beginning label> is implementation-dependent.
- 9) Subclause 13.13, “<for statement>”:
 - a) The implicit <beginning label> of a <for statement> with no explicit <beginning label> is implementation-dependent.
 - b) The <cursor name> used in the transformation of a <for statement> into a <while statement> is implementation-dependent, as are the <condition name> and the <SQL variable name> used in the <while statement> for getting diagnostics information.

Annex D
(informative)

Deprecated features

This Annex modifies Appendix D, "Deprecated features", in ISO/IEC 9075-2.

It is intended that the following features will be removed at a later date from a revised version of this part of ISO/IEC 9075:

No additional deprecated items.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

Annex E (informative)

Incompatibilities with ISO/IEC 9075-4:1999

This Annex modifies Appendix E, "Incompatibilities with ISO/IEC 9075-2:1999", in ISO/IEC 9075-2.

This edition of this part of ISO/IEC 9075 introduces some incompatibilities with the earlier version of Database Language SQL as specified in ISO/IEC 9075:1999. Unless specified in this Annex, features and capabilities of Database Language SQL are compatible with the earlier version of ISO/IEC 9075.

- 1) In ISO/IEC 9075-4:1999, it was not permitted to use a <statement label> to qualify an <SQL variable reference>. This gives rise to an incompatibility with ISO/IEC 9075-4:200n in the case where an SQL variable's name is the same as the <beginning label> of the innermost <compound statement> in which it is declared, the declared type of that variable is such that it has components that can be referenced using "dot notation" and one of those components has the same name as one of the other SQL variables declared in that same <compound statement>.

For example, if <compound statement> labeled CS simply contains the declaration of a variable named V and another variable named CS of type ROW(V INTEGER), then "CS.V" can be a reference to either the variable V or the field V of the variable CS and is thus a syntax error. In ISO/IEC 9075-4:1999, it unambiguously references the field.

- 1 list element deleted.
- 2) Insert after list element 10) The definition of "possibly nullable" with regard to <routine invocation> has been tightened. If all subject routines of a <routine invocation> specify PARAMETER STYLE GENERAL, then the <routine invocation> is known not nullable. In ISO/IEC 9075-4:1996, all <routine invocation>s were regarded as possibly nullable.
 - 3) Insert after list element 10) Some of the normative material previously specified in ISO/IEC 9075-4:1996 has been moved to ISO/IEC 9075-2. Although this will change any statement of conformance to this and other parts of ISO/IEC 9075, no incompatibilities other than those listed above have been introduced by the reorganization of this normative material.

SC32 N00745 = WG3:VIE-006 = H2-2002-008

Annex F (informative)

SQL Feature Taxonomy

This Annex modifies Appendix F, "SQL feature and package taxonomy", in ISO/IEC 9075-2.

This Annex describes a taxonomy of features of the SQL language.

Table 4, "Feature taxonomy for features outside Core SQL", contains a taxonomy of the features of the SQL language that are specified in this part of ISO/IEC 9075. In this table, the first column contains a counter that may be used to quickly locate rows of the table; these values otherwise have no use and are not stable — that is, they are subject to change in future editions of or even Technical Corrigenda to ISO/IEC 9075 without notice.

The second column, "Feature ID", specifies the formal identification of each feature and each subfeature contained in the table. The Feature ID is stable and can be depended on to remain constant. A Feature ID value comprises either a letter and three digits or a letter, three digits, a hyphen, and one or two additional digits. Feature ID values containing a hyphen and additional digits indicate "subfeatures" that help to define complete features, which are in turn indicated by Feature ID values without a hyphen. Only entire features are used to specify the contents of Core SQL and various packages.

The "Feature Name" column contains a brief description of the feature or subfeature associated with the Feature ID value.

Table 4, "Feature taxonomy for features outside Core SQL", modifies Table 35, "Feature taxonomy for features outside Core SQL", in ISO/IEC 9075-2.

Table 4—Feature taxonomy for features outside Core SQL

	Feature ID	Feature Name
1	P001	Stored modules
2	P001-01	<SQL-server module definition>
3	P001-02	<drop module statement>
4	P002	Computational completeness
5	P002-01	<compound statement>
6	P002-02	<handler declaration>
7	P002-03	<condition declaration>

Table 4—Feature taxonomy for features outside Core SQL (Cont.)

	Feature ID	Feature Name
8	P002-04	<SQL variable declaration>
9	P002-05	<assignment statement>
10	P002-06	<case statement>
11	P002-07	<if statement>
12	P002-08	<iterate statement>
13	P002-09	<leave statement>
14	P002-10	<loop statement>
15	P002-11	<repeat statement>
16	P002-12	<while statement>
17	P002-13	<for statement>
18	P002-14	<signal statement>
19	P002-15	<resignal statement>
20	P002-16	<control statement>s as the SQL-statement of an externally-invoked procedure
21	P003	Information Schema views
22	P003-01	MODULES view
23	P003-02	MODULE_TABLE_USAGE view
24	P003-03	MODULE_COLUMN_USAGE view
25	P003-04	MODULE_PRIVILEGES view
26	P004	Extended CASE statement
27	P005	Qualified SQL variable references
28	P006	Multiple assignment
29	P007	Enhanced diagnostics management

Index

Index entries appearing in **boldface** indicate the page where the word, phrase, or BNF nonterminal was defined; index entries appearing in *italics* indicate a page where the BNF nonterminal was used in a Format; and index entries appearing in roman type indicate a page where the word, phrase, or BNF nonterminal was used in a heading, Function, Syntax Rule, Access Rule, General Rule, Leveling Rule, Table, or other descriptive text.

<1992> • 7
<1999> • 7
<> • 125

— A —

abandoned • 63, 65
<action> • 17
activated • 11, 12, 13, 84, 112, 117, 139
active • 11, 12, 13, 98, 112, 116, 133
active completion condition • 11
active condition • 11
active exception condition • 11, 13
ALTER • 122, 124, 130, 131
<alter column definition> • 37
<alter domain statement> • 37
AND • 119, 120, 121, 122, 123
ANY • 125
applicable privileges • 31, 61
ARE • 52
array • 25, 32, 72, 74, 91, 92
array element error • 92
AS • 104, 119, 120, 121, 122, 123, 124
assertion • 48, 49, 55
<assertion definition> • 48
assignable • 32
<assigned row> • 64, 65, 89, 90
assignment • 1, 14, 15, 16, 27, 68, 74, 89, 90, 91, 92, 93, 107, 112, 141, 148
ASSIGNMENT • 112
<assignment source> • **89**, 90, 91, 92, 107
<assignment statement> • 14, 15, 16, 27, 68, **89**, 90, 93, 107, 112, 148
<assignment target> • **89**, 90, 91, 92, 107
<assignment target list> • **89**, 90
associated with • 10, 12, 17, 77, 83, 84, 88, 117, 141, 147
<asterisked identifier chain> • 29
AT • 19, 103
atomic • 16
ATOMIC • 16, 50, 79, 80, 81, 82, 101, 102, 103, 105
atomic SQL-statement • 16
attribute • 37
<attribute definition> • 37

ATTRIBUTES • 111, 112, 133, 147
AUTHORIZATION • 122, 124, 130, 131
<authorization identifier> • 17, 31, 53, 55, 127

— B —

based on • 3, 94, 97
base table • 38, 78, 125, 127, 129, 130
<basic identifier chain> • 27, 28
basis • 26, 27, 29
basis length • 26
BEGIN • 16, 79, 90, 101, 102, 103, 105, 112
<beginning label> • 26, 27, 29, **79**, 80, 99, 100, 101, 102, 103, 104, 142, 145
<between predicate part 2> • 94
boolean • 96
BOOLEAN • 105

— C —

candidate basis • 26, 29
capabilities • 145
cardinality • 92
CASCADE • 36, 38, 39, 40, 49, 51, 55, 65
CASE • 94
case not found for case statement • 95, 133
<case statement> • 14, 15, 16, 68, **94**, 95, 96, 112, 148
<case statement else clause> • **94**, 95
catalog • 52, 119, 120, 121, 122, 123, 126, 128, 129, 130, 131
<catalog name> • 52
CATALOG_NAME • 112, 114, 115, 119, 120, 121, 122, 123, 125, 129
character • 9, 33, 45, 47, 52, 53, 63, 64, 65, 94, 95, 111, 112, 117, 130, 131, 139, 141
<character like predicate part 2> • 94
character repertoire • 9
character set • 9, 33, 45, 53, 64, 130, 139, 141
<character set specification> • 52, 53
<character string literal> • 33, 139
CHARACTER_DATA • 127, 130
CHARACTER_SETS • 130
CHARACTER_SET_CATALOG • 122, 124, 130
CHARACTER_SET_NAME • 122, 124, 130

SC32 N00745 = WG3:VIE-006 = H2-2002-008

CHARACTER_SET_SCHEMA • 122, 124, 130
CHAR_SET_CAT • 124
CHAR_SET_NAME • 124
CHECK • 125, 127, 129
CHECK_REFERENCES • 125, 129
CLASS_ORIGIN • 112, 114, 115
Close • 73
CLOSE • 81, 85, 86, 100, 105
<close statement> • 73, 105
collating sequence • 46
collation • 46, 64
<colon> • 79, 101, 102, 103, 104
column • 26, 27, 37, 38, 39, 63, 64, 72, 90, 91, 104, 119, 125, 126, 131, 147
<column definition> • 37
column list • 39, 64
<column name> • 26, 64, 104
<column reference> • 27, 64, 90, 91, 131
COLUMNS • 125
COLUMN_NAME • 112, 114, 115, 119, 124, 125, 126
<comma> • 83, 88, 89, 114
COMMAND_FUNCTION • 112, 115, 117
<commit statement> • 80, 105
<common value expression> • 96
<comparison predicate part 2> • 94
compatible • 145
completion condition • 11, 12, 13, 81, 83, 85, 86, 111, 117
component • 10, 145
<compound statement> • 11, 12, 13, 14, 15, 16, 27, 29, 50, 68, 69, 79, 80, 81, 84, 90, 100, 101, 102, 103, 104, 109, 112, 142, 145, 147
condition • 1, 5, 6, 11, 12, 13, 14, 15, 16, 17, 21, 23, 33, 39, 55, 63, 64, 65, 79, 80, 81, 82, 83, 84, 85, 86, 87, 92, 94, 95, 96, 97, 98, 99, 101, 102, 103, 104, 109, 111, 112, 114, 115, 116, 117, 133, 139, 142, 147
CONDITION • 87, 105
<condition declaration> • 12, 14, 15, 79, 80, 82, 83, 87, 147
condition handling mode • 17, 116
<condition information item name> • 111, 114
<condition name> • 12, 21, 23, 80, 82, 83, 84, 87, 104, 112, 114, 116, 142
<condition value> • 12, 83, 84, 109
<condition value list> • 83, 84
CONDITION_IDENTIFIER • 19, 111, 112, 115, 117
considered to be defined • 82, 87, 115, 117
CONSTRAINT • 127
<constraint name> • 40, 49
CONSTRAINT_CATALOG • 112, 114, 115
CONSTRAINT_NAME • 112, 114, 115
CONSTRAINT_SCHEMA • 112, 114, 115
containing • 10, 12, 14, 22, 31, 37, 52, 53, 57, 80, 84, 101, 102, 103, 104, 139, 147
containing schema • 31
containing SQL • 10
<contextually typed row value expression> • 89, 91
<contextually typed source> • 89, 91
CONTINUE • 12, 83, 84, 105

CORRESPONDING • 39
corresponds to • 53, 107, 108, 112
CREATE • 52, 112, 119, 120, 121, 122, 123, 124, 125, 127, 129, 130, 131
current • 3, 9, 10, 21, 22, 31, 55, 61, 72, 82, 123
current authorization identifier • 9, 55
current privileges • 31
current SQL-session • 10, 21, 22
current user identifier • 61
CURRENT_PATH • 10
CURRENT_ROLE • 68
CURRENT_TIMESTAMP • 131
CURRENT_USER • 68, 119, 120, 121, 122
<cursor name> • 71, 72, 73, 75, 76, 80, 104, 142
<cursor sensitivity> • 104
<cursor specification> • 63, 72, 104
CURSOR_NAME • 112, 114, 115

— D —

Data • 3, 6, 71, 111, 145
DATA • 67, 127, 130
data exception • 92, 133
data type • 37, 38, 56, 65, 88, 114
<data type> • 37, 65, 88
date • 1, 3, 23, 26, 29, 31, 64, 65, 68, 76, 81, 82, 86, 89, 100, 102, 103, 143
<datetime value function> • 68
DECLARE • 57, 83, 87, 88, 90, 105
<declare cursor> • 11, 72, 79, 80, 109
declared local name • 80
declared type • 26, 88, 90, 91, 104, 107, 108, 145
DEFAULT • 105, 122, 124, 130, 131
<default clause> • 37, 88
<default option> • 68
<default schema name> • 9, 21, 52, 53
<default specification> • 91
DEFAULT_CHARACTER_SET_CATALOG • 122, 124, 130
DEFAULT_CHARACTER_SET_NAME • 122, 124, 130
DEFAULT_CHARACTER_SET_SCHEMA • 122, 124, 130
DEFAULT_SCHEMA_CATALOG • 122, 124, 130, 131
DEFAULT_SCHEMA_NAME • 122, 130, 131
DEFINED • 67
DEFINER • 63, 64, 65
Definition Schema • 3, 125
DEFINITION_SCHEMA • 119, 120, 121, 122, 123
DELETE • 64
<delete statement: positioned> • 64, 75
<delete statement: searched> • 64, 65
dependent • 10, 39, 53, 65, 74, 77, 80, 81, 101, 102, 103, 104, 119, 121, 141, 142
dependent on • 65
Description • 126, 127, 129, 130
descriptor • 9, 11, 17, 21, 22, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 49, 51, 52, 53, 54, 55, 56, 59, 60, 61, 63, 65, 68, 127
deterministic • 95
DIAGNOSTICS • 67, 111

diagnostics area • 11, 12, 13, 17, 69, 84, 85, 86, 112, 115, 116, 117, 139
 diagnostics exception • 112, 133
 direct result of executing an <SQL control statement> • 6
 <direct SQL statement> • 10, 12, 21, 22
 distinct • 94
 <distinct predicate part 2> • 94
 DO • 19, 102, 104, 105
 domain • 37, 44, 64, 68
 <domain definition> • 37
 <domain name> • 68
 DROP • 36, 38, 40, 49, 51, 55, 65, 112
 <drop assertion statement> • 49
 <drop behavior> • 55
 <drop character set statement> • 45
 <drop collation statement> • 46
 <drop column definition> • 39
 <drop column scope clause> • 38
 <drop data type statement> • 56
 <drop domain statement> • 44
 <drop module statement> • 9, 14, 36, 38, 40, 49, 51, 55, 65, 68, 69, 112, 137, 147
 <drop routine statement> • 36, 38, 40, 49, 51, 59
 <drop schema statement> • 9, 36
 <drop table constraint definition> • 40
 <drop table statement> • 41
 <drop transliteration statement> • 47
 <drop user-defined cast statement> • 60
 <drop user-defined ordering statement> • 51
 <drop view statement> • 43
 DYNAMIC • 112, 115, 117
 <dynamic declare cursor> • 109
 DYNAMIC_FUNCTION • 112, 115, 117

— E —

effective • 10, 11, 36, 38, 40, 49, 51, 53, 55, 65, 77, 78, 81, 85, 86, 88, 90, 100, 115, 127, 141
 effectively • 10, 11, 36, 38, 40, 49, 51, 53, 55, 65, 77, 78, 81, 85, 86, 90, 100, 115, 127, 141
 elements • 3, 19, 31, 139, 141
 element type • 92
 ELSE • 97
 ELSEIF • 19, 97
 <embedded exception declaration> • 109
 <embedded SQL host program> • 14, 109
 <embedded SQL statement> • 109
 <embedded variable name> • 91, 109
 empty • 69, 117
 enabled authorization identifiers • 53, 55
 enabled roles • 123
 ENABLED_ROLES • 119, 121, 122, 123
 END • 52, 79, 94, 97, 101, 102, 103, 104, 105
 <ending label> • 79, 80, 101, 102, 103, 104
 <equals operator> • 89, 95, 114
 exception • 5, 6, 11, 12, 13, 23, 81, 83, 92, 95, 96, 98, 101, 102, 103, 109, 111, 112, 114, 116, 117, 133, 139
 EXCEPTION • 12, 67, 83, 84

exception condition • 6, 11, 12, 13, 23, 81, 92, 95, 96, 98, 101, 102, 103, 112, 114, 116, 117
 executable routine • 31
 Execute • 12, 13, 104
 EXECUTE • 17, 31, 53, 55, 61, 62, 63, 127, 128
 <execute immediate statement> • 10, 21, 22
 execute privilege descriptor • 17, 127
 executing statement • 13, 81, 85, 96, 98, 101, 102, 103
 execution contexts • 16
 EXISTS • 122
 EXIT • 12, 13, 19, 83, 85
 externally-invoked procedure • 1, 12, 14, 67, 77, 148
 <externally-invoked procedure> • 1, 12, 14, 67, 77

— F —

FALSE • 105
 Feature F391 • 124
 Feature P001 • 7, 69, 135, 137
 Feature P004 • 96, 137
 Feature P005 • 27, 29
 Feature P006 • 93
 Feature P007 • 113
 Feature T011 • 122
 Feature T322 • 123
 FETCH • 105
 <fetch statement> • 72, 105
 <fetch target list> • 72
 <field name> • 89, 90, 92
 field reference • 27, 90, 92, 133
 <field reference> • 27
 FOR • 83, 87, 104, 105
 FOREIGN • 125, 127, 129, 130
 <for loop variable name> • 104
 <for statement> • 14, 15, 16, 68, 104, 112, 142, 148
 FOUND • 12, 67, 83, 84, 104, 105
 FROM • 33, 55, 119, 120, 121, 122, 123, 124, 125, 127, 129
 FS • 104, 105
 FUNCTION • 112, 115, 117

— G —

GENERAL • 145
 general <handler declaration> • 12, 84
 generally contain • 63, 68, 95
 <general value specification> • 25
 GET • 111
 <get diagnostics statement> • 111, 113
 GRANT • 119, 120, 121, 122, 123, 124
 GRANTEE • 120, 123, 127
 <grantee> • 61
 GRANTOR • 120, 123, 127
 <grantor> • 61
 <grant statement> • 61, 62

— H —

handle • 1, 6, 11, 12, 13, 14, 15, 16, 69, 79, 80, 81, 83, 84, 85, 86, 96, 98, 100, 101, 102, 103, 109, 112, 116, 117, 133, 139, 142, 147
 HANDLER • 19, 67, 83, 105

SC32 N00745 = WG3:VIE-006 = H2-2002-008

<handler action> • 12, 13, **83**, 84
<handler declaration> • 6, 12, 13, 14, 15, 79, 80, 81,
83, 84, 109, 147
<handler type> • **83**
HIERARCHY • 65
host language • 109
<host parameter specification> • 91
<host variable definition> • 109

— I —

identified • 9, 17, 21, 22, 37, 52, 53, 55, 57, 62, 63,
64, 65, 68, 80, 90, 91, 92, 116, 125, 127, 128,
129, 130, 131, 139, 141
identifier • 6, 9, 10, 17, 21, 22, 26, 27, 28, 29, 31, 53,
55, 61, 77, 79, 104, 111, 124, 126, 127, 128,
129, 130, 131, 141
<identifier> • 21, 26, 27, 29, 79, 104, 111
<identifier chain> • 26
identify • 17, 22, 139, 141
IF • 19, 97
<if statement> • 14, 15, 16, 68, **97**, 98, 112, 148
<if statement else clause> • **97**, 98
<if statement elseif clause> • **97**
<if statement then clause> • **97**, 98
immediate • 10, 15, 21, 22, 53, 64, 65, 80, 81, 90, 92,
95, 98, 99, 107, 109, 114, 116
immediately contain • 53, 64, 65, 80, 81, 90, 92, 98,
107, 109, 114, 116
impacted • 38
impacted dereference operation • 38
implementation-defined • 33, 52, 139
implementation-dependent • 10, 53, 74, 77, 80, 81,
101, 102, 103, 104, 141, 142
Implicit • 13
<implicitly typed value specification> • 89
IN • 119, 120, 121, 122, 123, 125, 127, 129
include • 1, 9, 10, 17, 22, 26, 29, 31, 36, 38, 39, 40,
49, 51, 52, 53, 55, 58, 61, 63, 64, 65, 95, 139
Information Schema • 1, 119, 122, 148
INFORMATION_SCHEMA • 119, 120, 121, 122, 123,
124, 125, 127, 129, 130
INFORMATION_SCHEMA_CATALOG_NAME • 119,
120, 121, 122, 123
inherit • 10
innermost • 13, 71, 72, 73, 75, 76, 83, 85, 114, 116,
145
<in predicate part 2> • 94
INSERT • 64
<insert column list> • 64
<insert statement> • 63, 64
INTEGER • 145
INTO • 105
IS_GRANTABLE • 120, 123, 127, 128
Iterate • 15
ITERATE • 19, 99, 112
<iterate statement> • 14, 15, 16, 68, **99**, 112, 148

— J —

JOIN • 119, 121

— K —

KEY • 111, 125, 127, 129, 130
known not nullable • 145

— L —

LANGUAGE • 57
<language clause> • 57
LAST • 122, 124, 130, 131
LEAVE • 13, 19, 100, 112
<leave statement> • 14, 15, 16, 68, **100**, 101, 102,
103, 105, 112, 148
<left paren> • 6, 27, 89
LENGTH • 112, 115, 117
<local cursor declaration list> • **79**, 80, 81, 100, 142
<local declaration> • **79**, 80
<local declaration list> • 26, 27, 29, **79**, 80, 81, 82,
100, 142
<local handler declaration list> • **79**, 80, 81, 100, 142
<local or schema qualified name> • 21
local temporary table • 9, 10, 32, 53, 77, 141
LOOP • 19, 101, 112
<loop statement> • 14, 15, 16, 68, **101**, 112, 142, 148

— M —

<match predicate part 2> • 94
maximum cardinality • 92
<member predicate part 2> • 94
<merge statement> • 63, 64, 65
MESSAGE_LENGTH • 112, 115, 117
MESSAGE_OCTET_LENGTH • 112, 115, 117
MESSAGE_TEXT • 112, 114, 115, 117
method • 12, 27, 51, 65, 89, 90
<method invocation> • 27
<method name> • 89, 90
<method reference> • 65
modified • 11, 27, 89, 90, 92
<modified field reference> • 27, **89**, 90, 92
<modified field target> • **89**, 90, 92
MODULE • 36, 38, 40, 49, 51, 52, 55, 62, 65, 78,
112, 119, 120, 121, 122, 123, 124, 125, 126,
127, 128, 129, 130, 131, 148
<module authorization clause> • 131
<module authorization identifier> • 131
<module function> • **57**
<module name> • 62
<module procedure> • **57**
<module routine> • 10, **57**
MODULES • 122, 124, 125, 127, 129, 130, 148
MODULE_AUTHORIZATION • 122, 124, 130, 131
MODULE_CATALOG • 119, 120, 121, 122, 123, 124,
125, 126, 127, 128, 129, 130
MODULE_COLUMN_USAGE • 119, 124, 125, 148
MODULE_CREATED • 122
MODULE_DEFINITION • 122, 124, 130, 131
MODULE_LAST_ALTERED • 122

MODULE_NAME • 120, 121, 122, 123, 124, 125,
126, 127, 128, 129, 130
MODULE_PRIVILEGES • 120, 122, 123, 127, 148
MODULE_SCHEMA • 120, 121, 122, 123, 124, 125,
126, 127, 128, 129, 130
MODULE_TABLE_USAGE • 121, 125, 129, 148
MORE • 115, 117
most appropriate • 12, 84, 117
most appropriate handler • 12, 84, 117
<multiple variable assignment> • **89**, 90, 93
<mutated target> • 90
<mutated target specification> • **89**, 90
<mutator reference> • 27, **89**, 90

— N —

<200n> • 7
Name • 21, 147
NAME • 52, 112, 114, 115, 119, 120, 121, 122, 123,
124, 125, 126, 127, 128, 129, 130, 131
NAMES • 52
NATURAL • 39
new transition variable column reference • 90
<non-reserved word> • **19**
no subclass • 133
NOT • 79, 80, 83, 84, 101, 102, 103, 105, 127, 130
not permitted • 145
null • 29, 92, 94, 107, 131, 133, 145
NULL • 127, 130
<null predicate part 2> • 94
<null specification> • 107
null value • 92, 131, 133
null value in array target • 92
null value in field reference • 92, 133

— O —

object • 6, 7, 9, 39, 61, 62, 64
object column • 64
<object column> • 64
<object name> • **62**
<octet like predicate part 2> • 94
OCTET_LENGTH • 112, 115, 117
ON • 55, 119, 120, 121, 122, 123, 124
<only spec> • 65
Open • 71
OPEN • 105
<open statement> • 71, 105
OPTION • 61, 65, 119, 120, 121, 122, 123, 124, 128
OR • 119, 120, 121, 122, 123, 125, 127, 129
outermost • 12, 80, 101, 102, 103, 104
<overlaps predicate part 1> • 94, 95
<overlaps predicate part 2> • 94, 95
owned by • 61, 119, 121

— P —

package • 147
Part 1 • 3
Part 11 • 3
Part 2 • 3
Part 3 • 7
<Part 3 conformance> • 7

Part 4 • 5, 6, 7, 111
<Part 4 conformance> • **6**, 7
<Part 4 module> • **6**
<Part 4 module no> • **6**, 7
<Part 4 module yes> • **6**, 7
<Part 4 yes> • **6**, 7
part of • 1, 5, 112, 135, 139, 141, 143, 145, 147
<path-resolved user-defined type name> • 21
<path specification> • 52
<period> • 26, 89
permitted • 14, 139, 145
persistent • 1, 9, 78
persistent base table • 78
possible scope tags • 26
possibly candidate routine • 31
possibly modifies SQL-data • 95
possibly nullable • 145
precede • 22, 109
<preparable statement> • 10, 21, 22
Prepare • 107
<prepare statement> • 10, 21, 22, 107
PRIMARY • 125, 127, 129, 130
privilege • 9, 17, 31, 53, 61, 62, 63, 64, 65, 120, 123,
127, 128
PRIVILEGE • 120, 122, 123, 127, 128, 148
privilege descriptor • 17, 53, 61, 127
PRIVILEGES • 120, 122, 123, 127, 148
<privileges> • 61, 62
PRIVILEGE_TYPE • 120, 123, 127, 128
PUBLIC • 119, 120, 121, 122, 123, 124, 127

— Q —

<qualified identifier> • 21, 22
<quantified comparison predicate part 2> • 94
query • 29, 39, 55, 63, 65, 104, 125, 129
<query expression> • 39, 55, 63, 65, 104, 125, 129
<query specification> • 29

— R —

recursive • 90, 97
REF • 38
<reference column list> • 39
referenced table • 39
<referenced table and columns> • 39
<reference resolution> • 65
REFERENCES • 39, 125, 127, 129, 130
referent • 26, 27, 29
refinable • 26, 29
REPEAT • 19, 103
<repeat statement> • 14, 15, 16, 68, **103**, 112, 142,
148
repertoire • 9
<reserved word> • **19**
RESIGNAL • 19, 67, 81, 85, 86, 112, 115, 116, 117
<resignal statement> • 11, 12, 13, 14, 68, 81, 85, 86,
112, 115, **116**, 148
resignal when handler not active • 116, 133
RESTRICT • 36, 39, 41, 43, 44, 46, 47, 55
result set • 11, 81, 85
result set cursor • 11, 81, 85

RETURNED_SQLSTATE • 112, 115, 117
 REVOKE • 55
 revoke destruction action • 63
 <revoke statement> • 39, 55, 62, 63
 <right paren> • 6, 27, 89
 role • 123, 127
 ROLES • 119, 121, 122, 123, 127
 ROLE_NAME • 119, 121, 122, 123, 127
 <rollback statement> • 80, 105
 ROUTINE • 36, 38, 40, 49, 51, 119, 124
 <routine body> • 53, 61, 63, 64, 65
 routine descriptor • 36, 38, 39, 40, 49, 55
 <routine invocation> • 10, 31, 53, 55, 61, 63, 95, 145
 <routine name> • 10, 26, 53
 routine SQL-path • 10
 ROUTINE_CAT • 119, 124
 ROUTINE_CATALOG • 119, 124
 ROUTINE_NAME • 119, 124
 ROUTINE_SCHEM • 119, 124
 ROUTINE_SCHEMA • 119, 124
 row type • 26, 29, 72
 <row value constructor> • 137
 <row value constructor element> • 137
 <row value constructor predicand> • 96
 <row value expression> • 137
 <row value predicand> • 94, 95, 96

— S —

<savepoint clause> • 80
 schema • 1, 6, 9, 10, 11, 12, 13, 17, 21, 22, 23, 31, 32, 35, 36, 47, 51, 52, 53, 55, 57, 58, 63, 68, 77, 78, 80, 81, 86, 99, 100, 101, 102, 103, 105, 126, 128, 129, 130, 131, 139, 141
 SCHEMA • 52, 112, 114, 115, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131
 <schema character set specification> • 53
 <schema definition> • 10, 21, 22, 31, 32, 35, 51, 52, 53, 57
 <schema element> • 35
 schema-level routine • 10, 17, 52, 58, 63
 <schema name> • 10, 21, 22, 23, 36, 52, 53, 55, 57, 77, 139, 141
 <schema name list> • 52, 53, 139
 <schema qualified name> • 9, 10, 21, 141
 <schema-resolved user-defined type name> • 22
 SCHEMATA • 119, 121, 122, 125, 129, 130
 SCHEMA_NAME • 112, 114, 115, 119, 121, 122, 130, 131
 SCHEMA_OWNER • 119, 121, 122
 scope • 1, 6, 12, 13, 16, 26, 29, 38, 65, 71, 72, 73, 75, 76, 77, 80, 81, 83, 84, 87, 101, 102, 103, 114, 116
 Scope • 1
 scope clause • 38
 scoped table • 65
 search condition • 39, 55, 63, 64, 65, 94, 95, 97, 98, 102, 103
 <search condition> • 39, 55, 63, 64, 65, 94, 95, 97, 98, 102, 103
 <searched case statement> • 94, 95
 <searched case statement when clause> • 94, 95
 SELECT • 39, 63, 64, 65, 119, 120, 121, 122, 123, 124, 125, 127, 129
 <select list> • 64, 65
 <select statement: single row> • 64, 65, 74
 <select target list> • 74, 141
 <semicolon> • 52, 79
 sensitivity • 104
 <separator> • 19
 sequence • 16, 46
 SESSION • 68
 SESSION_USER • 68
 SET • 88, 89, 90, 105, 114
 set of subject types • 22
 <set predicate part 2> • 94
 SETS • 130
 <set signal information> • 114, 115, 116
 SIGNAL • 19, 114
 <signal information item> • 114, 116
 <signal information item list> • 114
 <signal statement> • 11, 12, 14, 68, 112, 114, 115, 148
 <signal value> • 114, 116, 117
 <similar predicate part 2> • 94
 <simple case operand 1> • 94, 95, 96, 108, 137
 <simple case operand 2> • 94, 95, 96, 108, 137
 <simple case statement> • 94, 95, 108
 <simple case statement when clause> • 94, 95
 <simple target specification> • 25
 <simple value specification> • 25, 92, 114, 116, 117
 simply contain • 21, 22, 50, 63, 64, 65, 80, 81, 84, 90, 91, 92, 95, 97, 98, 99, 107, 108, 129, 145
 simply contained in • 21, 22, 65, 80, 81, 90, 92, 95, 97, 99, 107, 108, 129
 simply containing • 84
 <singleton variable assignment> • 89
 site • 91
 source • 64, 65, 89, 90, 91, 92, 107
 SPECIFIC • 36, 40, 49, 51
 specific <handler declaration> • 12, 84
 specific name • 36, 38, 40, 49, 51
 <specific name> • 36, 38, 40, 49
 specified by • 9, 10, 52, 53, 71, 72, 73, 75, 76, 83, 84, 87, 104, 109
 specify • 7, 10, 12, 39, 48, 50, 62, 80, 87, 101, 102, 103, 104, 114, 145, 147
 SQL • 57
 SQL-agent • 67
 SQL-client • 10, 12, 14, 22, 23, 53, 67, 77, 78, 104, 141
 SQL-client module • 10, 14, 22, 23, 53, 67, 77, 78, 104, 141
 <SQL-client module definition> • 22, 23, 53, 77, 78, 104, 141
 <SQL connection statement> • 68
 <SQL control statement> • 6, 68, 80, 81, 95, 98, 101, 102, 103, 104
 SQL-data • 13, 86, 95
 <SQL diagnostics information> • 111

- <SQL diagnostics statement> • **68**
 - <SQL edition> • 7
 - SQL-EXCEPTION • 12, 83, 84
 - SQL-implementation • 139
 - <SQL-invoked function> • 57
 - <SQL-invoked procedure> • 57
 - SQL-invoked routine • 1, 9, 10, 17, 31, 32, 36, 38, 40, 49, 51, 52, 53, 54, 55, 57, 58, 59, 61, 62, 63, 64, 65, 68, 77, 91, 95, 104, 105, 109
 - <SQL-invoked routine> • 1, 9, 52, 53, **57**, 68, 77, 104, 105, 109
 - <SQL object identifier> • **6**
 - SQL parameter • 25, 26, 27, 32, 72, 74, 89, 91, 104
 - <SQL parameter declaration list> • 26
 - SQL parameter name • 26, 32, 104
 - <SQL parameter name> • 26, 32, 104
 - SQL parameter reference • 27, 72, 74, 91
 - <SQL parameter reference> • 27, 72, 74, 91
 - SQL parameters • 25
 - <SQL parts> • **6**, 7
 - <SQL procedure statement> • 11, 12, 13, 14, 50, 53, 61, 68, 69, 79, 81, 83, 86, 95, 98, 100, 117, 137
 - <SQL provenance> • 6
 - SQL routine • 29, 36, 38, 39, 40, 49, 51, 55, 63, 64, 65
 - <SQL routine body> • 36, 38, 39, 40, 49, 51, 55, 63, 64, 65
 - SQL-schema • 10, 11, 13, 57, 99, 100
 - <SQL schema definition statement> • **68**
 - <SQL schema manipulation statement> • **68**
 - <SQL schema statement> • 6, 12, 31, 78, 80, 81, 101, 102, 103, 105
 - SQL-server • 1, 9, 10, 11, 12, 13, 17, 21, 22, 23, 31, 32, 35, 36, 38, 39, 40, 41, 43, 44, 45, 46, 47, 49, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 65, 68, 77, 78, 104, 112, 119, 120, 121, 122, 123, 126, 127, 128, 129, 130, 131, 139, 141, 147
 - SQL-server module • 1, 9, 10, 11, 13, 17, 21, 22, 23, 31, 32, 36, 38, 39, 40, 41, 43, 44, 45, 46, 47, 49, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 65, 68, 77, 78, 104, 112, 119, 120, 121, 122, 123, 126, 127, 128, 129, 130, 131, 139, 141, 147
 - SQL-server module authorization identifier • 9, 53
 - <SQL-server module character set specification> • 9, **52**, 53, 130, 141
 - <SQL-server module contents> • **52**
 - <SQL-server module definition> • 9, 10, 13, 21, 22, 31, 32, 35, **52**, 53, 54, 57, 68, 77, 78, 104, 112, 131, 141, 147
 - <SQL-server module name> • 9, 10, **21**, 23, 36, 38, 40, 49, 51, 52, 53, 55, 65, 139
 - <SQL-server module path specification> • 9, **52**, 53, 131, 139
 - <SQL-server module schema clause> • 9, **52**, 53, 131
 - SQL-session • 10, 13, 17, 21, 22, 69, 77, 85, 86, 115, 141
 - SQLSTATE • 11, 12, 23, 33, 67, 83, 84, 87, 105, 112, 114, 115, 116, 117, 133, 139
 - SQL-statement • 5, 6, 9, 12, 13, 14, 15, 16, 17, 50, 68, 81, 84, 86, 88, 99, 109, 112, 148
 - <SQL statement list> • **79**, 80, 81, 86, 94, 95, 97, 98, 99, *101, 102, 103, 104*
 - <sqlstate value> • **33**, 83, 84, 87, *114*, 115, 116, 117, 139
 - <SQL variable declaration> • 14, 15, 27, 37, 68, 79, 80, **88**, 109, 148
 - <SQL variable name> • **21**, 23, 26, 29, 32, 42, 48, 72, 80, 88, 90, 104, 109, 142
 - <SQL variable name list> • **88**
 - SQL variable reference • 27, 28, 29, 72, 74, 91, 145, 148
 - <SQL variable reference> • 25, **28**, 72, 74, 91, 145
 - <SQL variant> • 6
 - SQLWARNING • 12, 83, 84
 - SQL_IDENTIFIER • 125, 127, 129, 130
 - SQL_PATH • 122, 124, 130, 131
 - STACKED • 19, 67, *111*, 112
 - stacked diagnostics accessed without active handler • 112, 133
 - STATEMENT • 67
 - statement execution context • 16
 - <statement information item name> • 111
 - <statement label> • **79**, 80, 99, *100*, 101, 102, 103, 104
 - structured type • 26
 - STYLE • 145
 - SUBCLASS_ORIGIN • 112, 114, 115
 - subfield • 107, 108
 - subject routine • 10, 55, 63, 65, 95, 145
 - <submultiset predicate part 2> • 94
 - subrow • 91
 - successful completion • 12, 13, 33, 81, 84, 85, 86
 - superrow • 91
 - supertable • 65
 - SYSTEM_USER • 68
- T —
- Table • 10
 - TABLE • 119, 120, 121, 122, 123, 124, 125, 127, 129, 130
 - table constraint • 39, 40
 - <table expression> • 29, 64, 65
 - <table name> • 64, 77, 129
 - <table reference> • 63, 64, 65, 129
 - Tables • 10
 - TABLES • 127, 129
 - TABLE_CAT • 119, 121, 124, 125, 126, 129
 - TABLE_CATALOG • 119, 121, 124, 125, 126, 129
 - TABLE_NAME • 112, 114, 115, 119, 121, 124, 125, 126, 129
 - TABLE_SCHEM • 119, 121, 124, 125, 126, 129
 - TABLE_SCHEMA • 119, 121, 124, 125, 126, 129
 - target • 25, 27, 32, 64, 72, 74, 89, 90, 91, 92, 107, 141
 - <target array element specification> • 32, 72, 74, 91, 92

<target array reference> • **25**, 91
 <target specification> • **25**, 27, 72, 74, 89, 90, 91, 92
 <target table> • 64
 temporary • 9, 10, 32, 52, 53, 77, 78, 109, 141
 temporary table • 9, 10, 32, 53, 77, 78, 109, 141
 <temporary table declaration> • 9, 10, 52, 77, 78,
 109, 141
 <terminated local cursor declaration> • **79**, 80
 <terminated local declaration> • **79**
 <terminated local handler declaration> • **79**
 <terminated SQL statement> • **79**
 THEN • 94, 95, 97, 122
 TIME_STAMP • 130
 TO • 61, 119, 120, 121, 122, 123, 124
 <token> • 19
 transaction • 16
 transaction-initiating • 16
 transaction state • 16
 trigger • 13, 39, 50, 55, 86
 <trigger definition> • 50
 triggered action • 39
 <triggered SQL statement> • **50**
 TRIM • 33
 TRUE • 105
 Type • 10, 111
 TYPE • 67, 120, 123, 127, 128
 typed table • 65
 <type predicate part 2> • 94
 types • 10, 22, 104

— U —

UNDO • 12, 13, 19, 81, 83, 85
 unhandled completion condition • 12, 117
 unhandled exception condition • 12, 81, 96, 98, 117
 unhandled user-defined exception • 112, 117, 133
 <unqualified schema name> • 21, 22
 <unsigned value specification> • 27
 UNTIL • 19, 103
 UPDATE • 64
 <update source> • 64, 65
 <update statement: positioned> • 64, 76
 <update statement: searched> • 64, 65
 USAGE • 64, 65, 119, 121, 124, 125, 129, 148
 USER • 67, 68, 119, 120, 121, 122, 127, 130
 user-defined • 12, 21, 22, 51, 56, 60, 65, 90, 112,
 117, 133
 user-defined type • 21, 22, 56, 65, 90
 <user-defined type name> • 21
 user identifier • 61
 USERS • 127, 130
 USER_NAME • 127

— V —

valid • 3
 <value expression> • 27, 64, 65, 89, 91, 107, 108
 <value expression primary> • 26, 27, 65
 <value specification> • 25
 view • 1, 23, 39, 42, 43, 53, 55, 63, 81, 82, 86, 100,
 101, 102, 103, 111, 119, 120, 121, 122, 123,
 124, 125, 129, 148

VIEW • 119, 120, 121, 122, 123, 124
 view definition • 42
 <view definition> • 42
 viewed table • 42
 visible • 12

— W —

warning • 133
 WHEN • 94
 WHERE • 119, 120, 121, 122, 123
 <which area> • **111**, 112, 113
 WHILE • 19, 102, 105, 112
 <while statement> • 14, 15, 17, 68, **102**, 112, 142,
 148
 WITH • 61, 65, 119, 120, 121, 122, 123, 124, 128
 WITHOUT • 67
 without an intervening • 21, 22, 57, 77, 78, 80, 81,
 95, 98, 99, 100, 105, 141